

MT-PML-DS-R7-3P-DRB-600A-LT-DF-Z6-CZ-1Z6-M1

Non-Fused Disconnect Switch, 600 Amp, 38000V 3PH AC, 3-Pole 3-Wire, Pad Mount, NEMA 3R, 6-Way

Product ID: 304424



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PML-DS-R7-3P-DRB-600A-LT-DF-Z6-CZ-1Z6-M1 Disconnect Switch - Non-Fused Disconnect

Unit Type: Service Entrance Non-Fused Disconnect Switch, 6-Way

Line-In: N/A (Customer Provided)

Line-In Cord Cap: N/A (Customer Provided)

Line-In Connections: Terminal Lugs, Accepts #10-#14 AWG

Line-In Orientation: Bottom Feed

Voltage (V): 38000V AC Delta or Wye

Phase (PH): 3-Phase

Frequency (Hz): 60 Hz (60-Cycles)

Protection Method: N/A

Protection Type: N/A

Protection Fuses: N/A

Protection Ampacity: N/A

Mains Rating (Amps): 600A

Interrupting Rating: 600A RMS @ 38000V AC

Horsepower (Standard):

Max Motor Full Load Amps Rating:

Disconnect Means: Manual via Handle

Neutral Connection: -

Line-Out: N/A (customer provided)

Line-Out Cord Cap: N/A (customer provided)

Line-Out Connection: Terminal Lugs, Accepts #10-#14 AWG

Line-Out Orientation: Bottom Feed

Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door

Door: (1) Left Hinged Door w/ Pad Lockable Handle

Enclosure Material: 11GA Sheet Steel

Enclosure Finish: ANSI 49 Grey

Enclosure Type: NEMA 3R Ventilated

Ratings

NRTL Listed Service Equipment

NRTL Listed to UL 98 Dead Front Switch Boards

NEMA 3R Rated for Indoor or Outdoor Use

Made in the USA

Special Orders - Special Requirements

Mount: Pad Mount

Dimensions: -

Weight: -

Shipping Dimensions: -

Shipping Weight: -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The MT-PML-DS-R7-3P-DRB-600A-LT-DF-Z6-CZ-1Z6-M1 from Larson Electronics is a Power Distribution Non-Fused Disconnect Switch that is designed for reliable, safe, and convenient power distribution at industrial work sites. Designed for wall mounting installations, the disconnect switch is protected by a NEMA 3R rated, steel enclosure with a ventilated design.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MT-PML-DS-R7-3P-DRB-600A-LT-DF-Z6-CZ-1Z6-M1 service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with three-phase 38000V AC Delta or Wye, the disconnect switch features a manual operating handle. This 3-pole, 3-wire disconnect carries a 600A RMS at 38000V AC interrupt rating.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power.

Enclosure Design: The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI 49 grey finish. A ventilated design promotes natural cooling and improves performance.

Protective Construction: The disconnect is protected from the elements via a steel weatherproof enclosure with drip shield. Equipped with a hinged locking door, the panelboard carries a NEMA 3R rating for use in indoor or outdoor locations and protection from water, debris, corrosion, and external ice formation. This enclosure provides protection against falling rain and light ice formation. The NEMA 3R rated enclosure prevents beating rain from interfering with the successful operation of the apparatus or result in wetting of live parts and wiring within the enclosure under specified conditions. This unit is compatible with wall mounting installations.

Mount: Operators can mount the service entrance disconnect on walls.

Certification: This disconnect switch is NRTL listed to UL 98 dead front switchboards and NRTL listed for service equipment.


Customization: The MT-PML-DS-R7-3P-DRB-600A-LT-DF-Z6-CZ-1Z6-M1 can be customized to meet specific operating and power requirements. Example of customizations include:

- Making the fused disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single pole camlock connectors for quick connections
- Adding heaters for cold environments
- Aiding alarm relays for trip notification down stream
- Adding powering meters

Applications: This switchgear is suitable for indoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the

lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.







Frequently Asked Questions (FAQ)