Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X

100 kVA Isolation Transformer - 208V Wye Primary - 120/240V 1P Secondary - 3PH to 1PH, 316 SS/N4X

Product ID: 305909



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X Isolation Transformer
Phase: Three Phase to Single Phase
Frequency: 60 Hz
kVA: 100
Primary Voltage: 208Y V Wye (Three Phase)
Taps: 2 x 2.5% FCAN; 4 x 2.5% FCBN
Secondary Voltage: 120/240 V (Single Phase)
Winding Material: Aluminum
Insulation: 220°C
Temperature Rise: 150°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: 316 Stainless Steel NEMA Type 4X Stainless Steel
Finish: Natural
Dimensions: 29.00"-H x 17.00"-W x 22.50"-D
Weight: 265 lb
Mounting: Floor Mount

Ratings
NRTL Listed for United States and Canada
ANN Cooling
IP66 Rated
Isolation Transformer

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
E-mail: sales@larsonelectronics.com

The MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X from Larson Electronics is a 208V Wye 3 Phase to 1 Phase Energy Efficient Isolation Transformer that is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-

3P.1P-208Y-100KVA-120.240V-316SS.N4X provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 100 kVA, the MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X isolation transformer is a three phase to single phase unit with a primary voltage of 208Y V Wye. It also provides a secondary voltage of single phase 120/240 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The 316 stainless steel NEMA Type 4X enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP66.

Benefits: The MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-3P.1P-208Y-100KVA-120.240V-316SS.N4X achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


Dry Type Transformer Class AA
LARSON ELECTRONICS
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com
A14
WARNING
LARSON ELECTRONICS


X1
H3
X2
X4
H1
X3
H2
SO: 233332 – 001
233332


LARSON
ELECTRONICS
A14
WARNING
LARSON
ELECTRONICS



Frequently Asked Questions (FAQ)