

MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1

5 MVA Conservator Substation Transformer - 33000V Delta Primary, 6900Y/3984 Grounded Wye Secondary - ONAN, Grey

Product ID: 306034



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1 Conservator Substation Transformer

Transformer Type: Substation Power Transformer, Conservator Type
Transformer Configuration: Liquid Filled Conservator Substation Transformer
Transformer Feed Type: Radial Feed
Operation: Approved for Step-Up and Step-Down Operations
Phase: Three Phase
Capacity: 5 MVA (5000 KVA)
Vector Group: Dyn11
Primary Voltage: 33 kV (33000V)
Primary Voltage Switch: N/A
Primary Voltage Class: 35 kV Class
Primary Phasor: Delta
Primary BIL: 150 kV
Secondary Voltage: 6900Y/3984
Secondary Voltage Class: 8.7 kV Class
Secondary Phasor: Grounded Wye
Secondary BIL: 60 kV
Frequency: 60 Hz
Temperature Rise: 65°C
Insulation Rating: Class E Insulation - 120°C, 248°F
Cooling Class: ONAN; Self-Cooled
Forced Air (Fans): N/A
Cooling Radiator: N/A
HV Tap Changer: 17-Position ON-Load Tap Changer (OLTC)
HV Tap Qty: (8) FCAN Above Taps, (8) FCBN Below Taps
HV Tap %: 1.5% Taps
HV Tap Changer Switch Rating: 35 kV
HV Tap DETC Current Rating: 200A

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.29
Complies with ANSI / IEEE C57 12.34
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.110
Complies with ANSI / IEEE C57.12.131
Complies with ANSI / IEEE C62.11
Complies with ANSI / IEEE C62.22
Complies with ANSI / IEEE 386
Complies with ANSI / IEEE C2
Complies with ANSI / IEEE C37.47
Complies with ANSI Z535.4
Complies with ASTM D3487
Complies with ASTM D6871
Complies with NEMA 260-1996
Complies with 10 CFR Part 431
Complies with CSA C2.1-06
Complies with CSA C227.4
Complies with CSA C50
Complies with CSA C88
Complies with CSA C88.1
Complies with CSA C88-16
Complies with CSA C227.5

LV Tap Changer: N/A
LV Tap %: N/A
LV Tap Changer Switch Rating: N/A
LV Tap Changer Type: N/A
Impedance (Typical): 5.0% - 7.5% Typical (7% $\pm$ 5% Target)
Primary Connection Type: Live Front
Primary Termination Arrangement: Top Mounted Terminals
Primary Termination: Porcelain Bushings
Primary Connection Qty: (3) Primary Connections
Primary Bushing Rating: 35 kV Class, 150 kV BIL, 400A Continuous Current Rating
Primary Bushing Type: ABB Style Number 069W0412AN
Primary Bushing CT Qty: (3)
Primary Bushing CT Rating: 600:5 Ratio, MR Type, C400 (RF2.0) Accuracy
Primary Neutral Connection: N/A
Primary Surge Arrestors: Included Porcelain Surge Arrestors, type: Ohio Brass MVN060GA048AA
Primary Surge Arrestor Voltage Rating: 60 KV
Primary Surge Arrestor MCOV Rating: 48 KV
Primary Over Current Protection (OCP): N/A
Primary Over Current Protection Method: N/A
Primary Over Current Protection Holder: N/A
Primary Grounding Provisions: N/A
Secondary Connection Type: Live Front
Secondary Termination Arrangement: Top Mounted Porcelain Bushings
Secondary Connections: Porcelain Bushings
Secondary Connection Qty: (3)
Secondary Bushing Rating: 8.7 kV Class, 60 kV BIL, 1200A Continuous Current Rating
Secondary Bushing Type: PCORE Style PRC B-89111-55-70
Secondary Bushing CT Qty: (5)
Secondary Bushing CT Ratings: [(3) 1200:5 Ratio, MR Type, C400 (RF2.0) Accuracy], [(1) 900:5 Ratio, SR Type, C400 (RF2.0) Accuracy on (X1)] & [(1) 900:5 Ratio, SR Type, C400 (RF2.0) Accuracy on (X2)]
Secondary Over Current Protection (OCP): N/A
Secondary Neutral Connection: Included
Secondary Neutral winding BIL: 60 KV
Secondary Neutral Bushing Ratings: 8.7 KV Class, 60 KV BIL, 1200 A Continuous Current Rating
Secondary Neutral Bushing Type: PCORE Style PRC B-89111-55-70
Secondary Surge Arrestors: Included Polymer Surge Arrestors, type: Ohio Brass EVP00300-3001
Secondary Surge Arrestor Voltage Rating: 3 KV
Secondary Surge Arrestor MCOV Rating: 2.55 KV
Secondary Grounding Provisions: (1) NEMA Ground Bar attached to tank via (2) Welded Ground Bungs
Metering Current Transformer (CT): N/A
Metering Panel: N/A
Auxiliary Control Panel : N/A
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Rating: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Mineral Oil Insulating Fluid - Non-PCB Fluid
Fluid (Oil) Capacity*: TBD
Fluid (Oil) Weight*: TBD
Liquid Level Indicator: Analog Dial Gauge
Temperature Indicator: Analog Dial Gauge
Pressure/Vacuum Indicator: Analog Dial Gauge
Pressure Relief Device: Included, Automatic Action
Fault Indicator: Included, Buchholz Relay
Gas Sampler Valve: Included, Schrader Valve
Fill Valve: 1" NPT Port w/ Removable Bolt Plug
Fill Valve Location: Front Compartment
Drain Valve: 1" NPT Port w/ 5/8" NPT Sampler Valve
Drain Valve Location: Front Compartment
Conservator Tank: Included
Winding Material: Copper
Ambient Temperature Rating: 40°C

Complies with CSA C802-3
Complies with CSA C802.1

Features

Pentahead Bolt Entry Assembly
Hot Stick Included, HV Door Mount
NEMA 3R Wiring Compartment
Hinged Front Compartment Doors, Pad Lockable
Tamper Proof Housing
Non-PCB Insulating Fluid

Efficiency %: 98.00%

Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 85°C Reference Temp.

No Load Loss (in watts): TBD

Full Load Loss (in watts) at 100%: TBD

Total Load Loss (in watts) at 100%: TBD

Total Losses at 55°C LL Temp. & 20°C NL Temp.

Total Load Loss (in watts) at 50%: TBD

Note: Losses offered are typical only, not guaranteed

Labeling:

Externally Stencilled (Painted) KVA Rating
Externally Stencilled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

Factory Tests:

Winding Resistance Test
Insulation Resistance Test
Voltage Ratio Error Test
Short-circuit Impedance Test
No-load Loss (Wattage) Test
Load Loss (Wattage) Test
Induced Voltage Withstand Test
Separate Source Voltage Withstand Test
Pressure Integrity Test Test

Shipping:

Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets

Ambient Operating Temperature Range: -40°C to +40°C (-50°F to +104°F)

Sound Level: 66 dBA

Elevation (Altitude): 3300ft (1000 meters) Above Sea Level

Core Material: Grain Oriented Steel

Tank Material: Coated Steel

Cabinet Material: Coated Steel

Base Platform Material: Coated Steel

Portability: Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding

Housing Type: Metal Casing Liquid Filled Transformer

Enclosure Rating: NEMA 3R Weatherproof Wiring Cabinet, Sealed Tank

Seismic Rating: Yes

Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating

Finish Color: ANSI 61 Grey

Mounting: Pad Mounted

Conduit Opening: N/A

Tank Cover Access Handhole: N/A

Dimensions*: TBD

Dry Weight (w/o Oil)*: TBD

Total Weight (Liquid Filled)*: TBD

*Please note that numbers are approximate and subject to change

Pallet Skid Facing Outward Sides of Truck

Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1 Conservator Substation Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in indoor or outdoor locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This air tight transformer does not have doors and must be installed in a contained or protected area away from public access.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Transformer Features: The industrial transformer features a primary voltage of three-phase 33000V Delta and a secondary voltage of three-phase 6900Y/3984 Grounded Wye. This system carries the following rating: 5000 KVA. The unit has a primary radial feed and live front primary connections. We also offer systems with loop feed and dead front primary connections. This transformer features a 17-position OLTC tap changer on HV side with eight +/- 1.5% taps above and eight +/- 1.5% taps below to allow small changes for voltage. There are no load break switches, rapid rise relays, or protection fuses present on the system.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1 doesn't have fans or mounting provisions for fans. This system is completely sealed and features air tight construction. Designed for long-term performance, the transformer is maintenance free.

Temperature Rise: This unit features 65°C temperature rise for reduced heat waste, increased reliability and longer life. At 65°C temperature rise, the transformer offers 5000 KVA. The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Insulation Fluid: The MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1 features mineral oil insulation fluid (ONAN). We offer transformers with biodegradable or FR-3 fluids, if needed.

Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil.

When operating at high temperatures, biodegradable cooling liquid sustains up to 120% loan conditions, which helps preserve the transformer's lifespan and performance.

Gauges: The following gauges are included with the system: liquid level, temperature and pressure/vacuum gauges. Standard liquid level, temperature, and pressure/vacuum gauges are analog, manual reading types. These gauges do not have alarm contacts.

Fault Pressure Devices: There are no fault pressure devices on the unit. Fault pressure devices are used to detect high rates of pressure rise within the tank.

Rapid Rise Relay: There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.

Surge arresters: This system comes with surge arresters on the primary and secondary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without high elbow surge arresters that have mounting provisions for customer-provided surge arresters.

Load Breaker Switch: The transformer is not equipped with a load breaker switch.

Valves: The MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1 is equipped with a pressure relief valve, fill valve, and drain valve with sampler port.

Protection Fuses: This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, up stream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.

Terminal Connections: The primary and secondary terminal connections are located on the top of the transformer. We can configure the location to be side located or side located for both the high voltage and low voltage sides.

Mount: This conservator transformer should be installed in a contained, fenced, or protected area.

Benefits: The MT-PSTC-R7-3P-DMC-5MVA-GNZ-HT-LT-X6-BM-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)