

VFD-6.6KV-3P-3860HP-N3R

3860 HP Variable Frequency Device - 6600 V AC Input/Output 3PH - 252 Amps - IP42

Product ID: 308572



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

VFD-6.6KV-3P-3860HP-N3R Variable Frequency Device

Unit Type: Variable Frequency Device

Dimensions: W4500 x D1525 x H2930 mm

Weight:

Input Voltage: 6600V AC 3PH

Output Voltage: 6600V AC 3PH

Output Current: 252A

Operating Frequency: 0 - 400 Hz

Switching Frequency: 2 - 8 kHz

Nominal Switching Frequency: 2.5 kHz

HP: 3860

KVA: 2880

Digital Inputs: 8 Inputs

Digital Outputs: 3 Outputs - Relay

Analog Input/Output: 3 Inputs, 2 Outputs

Insulation Resistance: > 1 MOhm 500 V DC for 1 minute to earth

Noise Level: 69.9 dB 86/188/IEC

Communication Protocol: PROFIBUS-DP

Communication Interface: RS-232/422/485

Operating Position: Vertical +/- 10 Degree

THDI: <= 48 % full load IEC 61000-3-12

Pollution Degree: 2 EN/IEC 61800-5-1

Vibration Resistance: 1.5 mm peak to peak 2...13 Hz IEC 60068-2-6 1 gn 13...200 Hz IEC 60068-2-6

Shock Resistance: 15 gn 11 ms IEC 60068-2-27

Relative Humidity: 5...95 % without condensation IEC 60068-2-3

Operating Altitude: 1000...4800 m with current derating 1 % per 100 m <= 3280.84 ft

Features/Ratings

IP00 IEC 61800-5-1

IP00 IEC 60529

Forced Convection Cooling

16 Preset Speeds

Integrated Filter EN/IEC 61800-3 Cat. C3

IP21

EN/IEC 61800-3

EN/IEC 61800-3 environment 1 Cat. C3 & 2 Cat. C3

UL 508C

EN/IEC 61800-5-1

IEC 61000-3-12

IEC 60721-3

IEC 61508

IEC 13849-1

ATEX zone 2/22

CSA

UL

CE

(1000 m) without derating

Chemical Pollution Resistance: Class 3C3 EN/IEC 60721-3-3

Dust Pollution Resistance: Class 3S3 EN/IEC 60721-3-3

Integrated Communications: ModBus Serial, ModBus TCP, Ethernet

Operating Temp: -15°C to +50°C

Materials: -

Mounting: Surface

Color: Gray

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics VFD-6.6KV-3P-3860HP-N3R Variable Frequency Drive is suitable for improving AC motor performance in industrial operations. This fan-cooled unit features three-phase 6600V AC input voltage and 6600V AC output voltage compatibility (252-amp output current). The IP42 rated device supports three digital inputs, two analog outputs, five analog inputs.

The VFD-6.6KV-3P-3860HP-N3R offers accurate AC motor control in industrial facilities. This unit is compatible with three-phase 6600V AC input voltage and 6600V AC output. Designed for steady speed error, fast torque rise and protection from resonance vibrations, the device provides an output current of 252 amps. This VFD comes with several features to improve motor control. The unit comes with seven preset speeds and three critical speed lockout bands. Operators can set ramp to stop or coast to stop options. For fault functions, the VFD offers the following pre-programmed features: AI (1,2 loss), encoder error, panel loss, assistant external fault, motor thermal protection, stall protection, underload, motor phase loss, ground fault and communications fault. The unit also comes with standard pre-programmed safety features: safe torque off motor and off drive, motor phase break motor and drive, overheating, short-circuit, overspeed, overvoltage, overload, phase loss, undervoltage, overcurrent, and thermal protection of the motor and drive. The motor control profile includes optimized torque mode, constant torque standard and variable torque standard, with a permanent magnetic motor, PROFIBUS-DP Communication Protocol, RS-232/422/485 Communication Interface.

The VFD-6.6KV-3P-3860HP-N3R is protected by a IP42 rated enclosure and may be mounted on compatible surfaces. This device measures W4500 x D1525 x H2930 mm.

Applications: Speed control of AC motors, industrial machines, large compressors, energy savings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)