Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-DOE16-3P-480D-15KVA-208Y.120-N12

15 kVA 3PH DOE Transformer, 480V Delta Primary, 208Y/120 Wye-N Secondary, N12, Ventilated, 60 Hz, Aluminum

Product ID: 309026



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-3P-480D-15KVA-208Y.120-N12 DOE Efficiency Isolation Transformer

Transformer Type: Isolation Transformer
Transformer Configuration: Dry Type
Phase: Three Phase
Frequency: 60 Hz
Primary Voltage: 480V AC
Primary Connection: Delta
Primary Lug Kit: Included, (1) DASKP100
Capacity: 15 KVA
Secondary Voltage: 208Y/120V AC
Secondary Connection: Wye-N
Secondary Lug Kit: Included, (1) DASKGS100
Knockouts: Sides
Tap Changer: 6-Position Tap Changer
FCAN (Above) Taps: 2
FCAN (Above) Taps: 4
Tap %: 2.5
Impedance: 2.5-6.5% Typical
Efficiency @ 35% Load: ~98%
Winding Material: Aluminum
Primary Termination (Std): Terminal Lugs
Secondary Termination (Std): Terminal Lugs
Termination Access: Front Access Cover
Mounting: Floor
Cooling: Air/Dry
Insulation Class: 220°C (Class H)
Temperature Rise: 150°C
Sound Level: 39 dB(A)
Enclosure Material: NEMA Type 12 Heavy Duty Ventilated - Steel

Approvals/Ratings

NRTL Listed for United States
NRTL Listed for Canada
NEMA 12 Indoor Steel Enclosure
Meets or Exceeds NEMA ST-20 Standards
DOE Efficiency Isolation Transformer
Distribution Type Transformer
UL Labeled
Built to UL-50 Standards
Seismic Qualified for Earthquake Loads
RoHS
CE Certified

Finish: ANSI 49 Grey
Dimensions: 19.37"-L x 24.39"-W x 25.5"-H
Weight: 290 lb
Shipping Method: Pallet Freight - LTL
Shipping Weight: 355 lb
Shipping Dimensions: 48"-L x 40"-W x 40"-H

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-DOE16-3P-480D-15KVA-208Y.120-N12 from Larson Electronics is a Three Phase 480V to 208Y/120 15 KVA DOE Efficiency Transformer that is powerful, reliable, and designed with the environment in mind. Suitable for indoor applications, the MT-DOE16-3P-480D-15KVA-208Y.120-N12 provides increased reliability and protection against critical equipment failures. This 15 KVA isolation is designed for distribution loads and potential seismic activity. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The MT-DOE16-3P-480D-15KVA-208Y.120-N12 DOE Efficiency transformer is a three phase transformer with a 15 KVA capacity rating. This isolation transformer is configured with an input voltage of 480V Delta 3-Phase AC on the primary side and an output voltage of 208Y/120 Wye-N 3-Phase AC on the secondary side. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The standard NEMA Type 12 enclosure makes the unit suitable for indoor applications and is designed to be floor mounted. Wall mount brackets or additional mounting accessories can be purchased separately. This 15 KVA distribution transformer features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-DOE16-3P-480D-15KVA-208Y.120-N12 480V to 208Y/120 general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

The MT-DOE series of transformers from Larson Electronics meet or exceed efficiency standards for United States and Canada. This results is overall lower cost of ownership throughout the life of the transformer.

Safety: The MT-DOE16-3P-480D-15KVA-208Y.120-N12 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock and injury. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-3P-480D-15KVA-208Y.120-N12 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.


Applications: Converting 480V local grid power to 208Y/120 for on-site equipment. This 15 KVA power transformer is ideal for sensitive equipment such as CNC equipment, computers, medical devices, ovens, or laboratory instruments. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units

almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Wiring Diagram

WARNING: *DO NOT SERVICE WHILE ENERGIZED!*

MT-DOE16-3P-480D-15KVA-208Y.120-N12



PRIMARY VOLTS	
CONNECT LINES TO H1, H2, H3	
TAP	VOLTAGE
1	504
2	492
3	480
4	468
5	456
6	444
7	432
SECONDARY VOLTS	
CONNECT LINES	VOLTAGE
X1, X2, X3	208
X0-X1, X0-X2, X0-X3	120

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com




Larson Electronics
1-800-369-6671



Frequently Asked Questions (FAQ)