

MT-ATX-3P-208V-20.4KVA-235V-N3R

20.4 kVA Autotransformer - 208V Primary Voltage - 235V Secondary Voltage - NEMA 3R - 60Hz

Product ID: 309064



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ATX-3P-208V-20.4KVA-235V-N3R Autotransformer

Phase: Three Phase
Frequency: 60Hz
kVA: 20.4
Primary Voltage: 208V AC
Primary Connection: -
Secondary Voltage: 235V AC
Secondary Connection: -
Output Amps: 50A @ 50% Duty
Taps: TBD
Impedance: -
Efficiency @ 35% Load: -
Winding Material: Aluminum
Primary Termination (Std): Terminal Lugs
Secondary Termination (Std): Terminal Lugs
Mounting: Floor or Wall
Cooling: Air/Dry
Insulation: 180°C
Temperature Rise: 135°C
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated - Steel
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: -
Weight: 60 lbs

Approvals/Ratings

Listing: UL Listed
CSA Certified
Autotransformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The MT-ATX-3P-208V-20.4KVA-235V-N3R 208V 3 Phase Energy Efficient Autotransformer from Larson Electronics is powerful, reliable and

designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ATX-3P-208V-20.4KVA-235V-N3R provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Transformer Features: With a transformer rating of 20.4 kVA, the MT-ATX-3P-208V-20.4KVA-235V-N3R transformer is a three phase unit with a primary voltage of 208V AC. It also provides a secondary voltage of 235V AC. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be either floor or wall mounted. The unit also features 180° insulation with a 135°C temperature rise.

Benefits: The MT-ATX-3P-208V-20.4KVA-235V-N3R general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ATX-3P-208V-20.4KVA-235V-N3R is an autotransformer which means that it has the ability to adjust the supply voltage to match specific load requirements when load isolation from the supply line is not required. Autotransformers are typically used in distribution systems that require small voltage corrections during operation.

Applications: Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.









Frequently Asked Questions (FAQ)