

MPD-DS-WM-NFDS-3P-3W-600V-400A-DF-BM-N4X

400 Amp Non-Fused Manual AC Disconnect Safety Switch - 600V AC - 3-Pole - NEMA 4X

Product ID: 309071



Image: MPD-DS-WM-NFDS-3P-3W-600V-400A-DF-BM-N4X

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-DS-WM-NFDS-3P-3W-600V-400A-DF-BM-N4X Disconnect Switch - Non Fused

Disconnect

Unit Type: Service Entrance Non Fused Disconnect Switch

Line-In: N/A (customer provided)

Line-In Cord Cap: N/A (customer provided)

Line-In Connections: Terminal Lugs

Line-In Orientation: Bottom Feed

Voltage (V): 480V AC Delta or Wye

Phase (PH): 3-Phase

Frequency (Hz): 60 Hz (60-Cycles)

Protection Method: N/A (customer provided)

Protection Type: N/A (customer provided)

Protection Ampacity: -

Mains Rating (Amps): 400A

Interrupting Rating: 200 kA @ 600V AC

Horsepower (Standard): 50 HP at 240V, 100 HP at 480V, 125 HP at 600V

Horsepower (Max): 125 HP at 240V, 250 HP at 480V, 350 HP at 600V

Disconnect Means: Manual via Handle

Neutral Connection: -

Line-Out: N/A (customer provided)

Line-Out Cord Cap: N/A (customer provided)

Ratings

NRTL Listed Service Equipment

NRTL Listed to UL 891 Dead Front Switch Boards

NEMA 4X Rated for Indoor and Outdoor Use

Made in the USA



Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0

Line-Out Orientation: Bottom Feed

Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door

Door: (1) Left Hinged Door w/ Pad Lockable Handle

Enclosure Material: 304 Stainless

Enclosure Finish: Natural Metal Finish

Enclosure Type: NEMA 4X Ventilated

Mount: Wall Mount

Dimensions: 27.76"-W x 50.31"-H 14.97"-D

Weight: 800 lbs

Shipping Dimensions: 58"-W x 44"-L x 98"-H

Shipping Weight: 850 lbs

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-DS-WM-NFDS-3P-3W-600V-400A-DF-BM-N4X Power Distribution Non Fused Disconnect Switch is designed for reliable, safe and convenient power distribution at industrial work sites. Designed for wall mounting installations, the disconnect switch is protected by a NEMA 4X rated, 304 Stainless steel enclosure with a ventilated design.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

The MPD-DS-WM-NFDS-3P-3W-600V-400A-DF-BM-N4X service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with three-phase 600V AC Delta or Wye, the disconnect switch features a manual operating handle. This 3-pole, 3-wire disconnect carries a 200 kA at 600V AC interrupt rating.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power.

Enclosure Design: The disconnect switch is protected by an 304 Stainless Steel enclosure with Natural Metal Finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 4X rated for protection against water, moisture and debris. This rating allows the non fused disconnect to be used in indoor and outdoor areas.

Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the service entrance disconnect on walls.


Customization: The MPD-DS-WM-NFDS-3P-3W-600V-400A-DF-BM-N4X can be customized to meet specific operating and power requirements. Example of customizations include:

- Making the non-fused disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single pole camlock connectors for quick connections
- Adding heaters for cold environments
- Aiding alarm relays for trip notification down stream
- Adding powering meters

Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

8	7	6	5	4	3	2	1
↓							
REV	DESCRIPTION						DATE
A	PRODUCTION RELEASE						9/28/2026
MPD-DS-WM-NFDS-3P-3W-600V-400A -DF-BM-N4X							
							
8	7	6	5	4	3	2	1



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs