Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ

**7.5 kVA Isolation Transformer - 208Y/120V Wye Primary - 220V (L+N) Euro Secondary - NEMA 3R - Fully Potted - 3 Phase to 1 Phase - 50/60 Hz**

**Product ID: 309114**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ Fully Potted Isolation Transformer**

**Phase:** Three Phase to Single Phase
**Frequency:** 50/60 Hz
**kVA:** 7.5
**Primary Voltage:** 208Y/120 V Wye 3PH
**Secondary Voltage:** European 220 V (L+N) 1P
**Winding Material:** Copper
**Taps:** None
**Insulation:** 180°C
**Temperature Rise:** 115°C
**Primary Termination:** -
**Secondary Termination:** -
**Sound Level:** 45 dB
**Enclosure Material:** NEMA Type 3R Heavy Duty Ventilated
**Finish:** ANSI 61 Grey Finish
**Dimensions:** 10.02"-H x 5.40"-W x 5.13"-D
**Weight:** 24 lb

**Approvals/Ratings**

NRTL Listed for United States and Canada
IP14
ANC Cooling
Fully Potted / Encapsulated
Isolation Transformer

**Special Orders - Special Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**E-mail:** sales@larsonelectronics.com

**The MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ from Larson Electronics is a 208Y/120 V Wye 3 Phase to 1 Phase Energy Efficient 50/60 Hz Fully Potted Isolation Transformer that is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ provides increased reliability, protection against critical equipment failures and an extra level of protection by isolating the power source**

**from the connected device. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.**

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS***

**Transformer Features:** With a transformer rating of 7.5 kVA, the MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ fully potted isolation transformer is a three phase to single phase unit with a primary voltage of three phase 208Y/120 V Wye. It also provides a secondary voltage of 220 V single phase (L+N). This L+N model is considered European 220 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted, 50/60 Hz unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features a 180°C insulation with a 115°C temperature rise and is rated IP14.

**Benefits:** The MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.


This fully potted, 50/60 Hz transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated wall mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

**Safety:** The MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ is a 50/60 Hz encapsulated isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-FP-3P.1P-208Y-7.5KVA-220V.EU-N3R-50HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

**Applications:** Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.







# Frequently Asked Questions (FAQ)