Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1

16/20 MVA Conservator Substation Transformer - 230000Y/132790 x 218500Y/126151 Wye-N Primary, 13800Y/7968 Wye-N Secondary, 13800V Delta Tertiary Winding, ONAN/ONAF

Product ID: 309477



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1 3PH Substation Transformer

Transformer Type: Power Transformer, Conservator-Type
Transformer Configuration: Liquid Filled Substation
Transformer Feed Type: Radial Feed
Phase: Three Phase
Capacity (w/o Fans): 16 MVA (16000 KVA)
Capacity (w/ Fans): 20 MVA (20000 KVA)
Vector Group: YNyn0+d
Primary Voltage: 230000Y/132790 x 218500Y/126151
Primary Line Voltage Class: 395 kV Class
Primary Neutral Voltage Class: 140 kV Class
Primary Voltage Switch: Included
Primary Phasor: Wye-N
Primary Line BIL: 950 KV
Primary Neutral BIL: 325 KV
Secondary Voltage: 13800Y/7968
Secondary Line Voltage Class: 28 kV Class
Secondary Neutral Voltage Class: 28 kV Class
Secondary Phasor: Wye-N
Secondary Line BIL: 75 kV
Secondary Neutral BIL: 75 kV
Tertiary Winding: Included
Tertiary Winding Voltage: 13800V
Tertiary Winding Class: 28 kV

Ratings

Meets/Exceeds IEC 60076 Ratings
Non-PCB Insulating Fluid
Tamper Proof Housing
Class A Insulation
Outdoor

Tertiary Winding BIL: 75 kV
Tertiary Winding Phasor: Delta
Tertiary Winding Power Rating: 5 MVA
Frequency: 60 Hz
Oil Temperature Rise: 60°C
Winding Temperature Rise: 65°C
Cooling Class: ONAN/ONAF
Forced Air (Fans): Included
Tap Changer: 5-position Off-Load Tap Changer
Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps
Tap %: 2.5%

Tap Changer Switch Location: High Voltage (HV) Front Compartment

Impedance: 12.04 % @ 20 MVA

Primary Connection Type: Dead Front

Primary Termination: Spade Terminals

Primary Connection Qty: (4)

Primary Surge Arrestors: N/A

Primary Surge Arrestor Voltage Rating: N/A

Primary Surge Arrestor MCOV Rating: N/A

Primary Over Current Protection (OCP): N/A

Primary Over Current Protection Method: N/A

Primary Over Current Protection Holder: N/A

Primary Line Current Transformer: Included, (3) [Bushing Type, 400:5 SR, 100 VA Burden Rating, 5P20 Accuracy Class] Per Each Phase, (1) [Bushing Type, 400:5 SR, 100 VA Burden Rating, 0.3 Accuracy Class] Per Each Phase & (1) [Bushing Type, 100:2 SR, 10 VA Burden Rating, 10P2 Accuracy Class] On Phase-2 (V-Phase)
Primary Neutral Current Transformer: Included, (1) [Bushing Type, 200:5 SR, 25 VA Burden Rating, 5P20 Accuracy Class]
Secondary Connection Type: Live Font

Secondary Connections: Spade Terminals

Secondary Connection Qty: (4)

Secondary Over Current Protection (OCP): N/A

Secondary Line Current Transformer: Included, (2) [Bushing Type, 1200:5 SR, 25 VA Burden Rating, 5P20 Accuracy Class] Per Each Phase, (1) [Bushing Type, 1200:5 SR, 45 VA Burden Rating, 0.3 Accuracy Class] Per Each Phase
Secondary Neutral Current Transformer: Included, (1) [Bushing Type, 1200:5 SR, 25 VA Burden Rating, 5P20 Accuracy Class]

Grounding Provisions: (1) Grounding lug, accepts #2 copper

Metering Current Transformer (CT): N/A

Metering Panel: N/A

Control Panel: Buchholz Relay (alarm and trip), Pressure Relief Device (alarm and trip), Oil Level Indicator (alarm and trip), Dehydrating Breather, Oil Temp (alarm and trip), Coil Winding Temp (alarm and trip)
System Controls: AVR Control and Monitors, Fan Controls, Transformer Alarms and Trips (indicator lights and flags), Tap Changer Control and Monitoring; Current, Voltage Oil Level, Temperature Monitoring and Readouts
Load Break Switch: N/A

Load Break Switch Qty: N/A

Load Break Switch Location: N/A
Efficiency Standard(s): Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Mineral Oil Insulating Fluid - Non-PCB Fluid
Fluid Capacity: TBD

Fluid Weight: 39,683 lbs

Liquid Level Indicator: Analog Dial Gauge
Temperature Indicator: Analog Dial Gauge - Measuring Oil and Coil Temperature
Pressure/Vacuum Indicator: Analog Dial Gauge
Pressure Relief Device: Included, Automatic Action
Fill Valve: Removable Bolt
Fill Valve Location: Front Compartment
Drain Valve: Included, w/ Sampler
Drain Valve Location: Front Compartment
Winding Material: Copper
Ambient Temperature Rating: 55°C
Sound Level: Complies With NEMA TR-1

No Power Factor Efficiency @ 100% Load: 99.46%
No Power Factor Efficiency @ 75% Load: 99.55%
No Power Factor Efficiency @ 50% Load: 99.60%
No Power Factor Efficiency @ 25% Load: 99.55%
0.8 Power Factor Efficiency @ 100% Load: 99.33%
0.8 Power Factor Efficiency @ 75% Load: 99.43%
0.8 Power Factor Efficiency @ 50% Load: 99.51%
0.8 Power Factor Efficiency @ 25% Load: 99.44%
No Load Loss: 13.5 KW @ 16 MVA
Full Load Loss: 73 KW @ 16 MVA
Note: Losses offered are typical only, not guaranteed

Elevation Rating: 3300ft (1000 meters) Above Sea Level
Core Material: Grain Oriented Silicon Steel
Tank Material: Coated Steel
Cabinet Material: Coated Steel
Base Platform Material: Coated Steel
Housing Type: Compartmental Cabinet w/ Doors, HV Compartment Left, LV Compartment Right
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)
Mounting: Supporting Structures
Conduit Opening: N/A
Dimensions: TBD
Total Weight: 105,822 lbs
*Please note that numbers are approximate and subject to change

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1 Conservator Substation Transformer from Larson Electronics offers powerful, reliable and efficient power distribution in outdoor locations. The low operating costs, low heat emissions and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The conservator transformer should be installed on supporting structures.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The industrial transformer features a dual primary voltage of three-phase 230000Y/132790 x 218500Y/126151 Wye-N and a secondary voltage of three-phase 13800Y/7968 Wye-N. This system is dual rated for 16 MVA (16,000 KVA) [Natural Cooled] and 20 MVA (20,000 KVA) [Fan Cooled]. This transformer features a 5-position tap changer with two, +/- 2.5% taps above and two, +/- 2.5% taps below to allow small changes for voltage. The tap changer offers automatic action (automatic voltage sensing) with manual override. We offer systems with loop or radial feed, as well as dead front or live front primary connections.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1 has fans for forced air cooling. This non-sealed system features breathers for cooling when operating temperatures increase.

Temperature Rise: This unit features 65°C temperature rise for reduced heat waste, increased reliability and longer life. The transformer meets standard ANSI/IEEE efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Insulation Fluid: The MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1 features mineral oil fluid (ONAN/ONAF). We offer transformers with biodegradable or FR-3 fluids, if needed.

Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% loan conditions, which helps preserve the transformer's lifespan and performance.

Gauges: The following gauges are included with the system: liquid level, temperature and pressure/vacuum gauges. Standard liquid level, temperature and pressure/vacuum gauges are analog, manual reading types.

Fault Pressure Devices: There are no fault pressure devices on the unit. Fault

pressure devices are used to detect high rates of pressure rise within the tank.
Rapid Rise Relay: There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.
Surge arresters: This system does not come with surge arresters on the primary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without high elbow surge arresters that have mounting provisions for customer-provided surge arresters.
Load Breaker Switch: The transformer does not have a load breaker switch.
Valves: The MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1 is equipped with a pressure relief valve, fill valve and drain valve with sampler port.
Protection Fuses: This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, up stream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.
Mount: This conservator substation should be installed on supporting structures, such as the roof of the transformer main tank.
Benefits: The MT-PSTC-R7-3P-YXN.EXM-16MVA-YMP-HT-LS-A6-BMF-CZ-1ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)