

MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU

28 kVA Isolation Transformer - 400V Delta Primary Voltage - 400V Delta Secondary - 60 Hz/N3R, Copper/66.74A RC

Product ID: 309911



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU Isolation Transformer

Phase: Three Phase
Frequency: 60 Hz
kVA: 28 KVA
Primary Voltage: 400D
Primary Connection: Delta
Secondary Voltage: 400D
Secondary Connection: Delta
Taps: -
Rated Current: 66.74A
Single Circuit Power Supply: 66.74A
Total Power Supply: 217.30A
Power Factor: 0.95
Primary Termination (Std): -
Secondary Termination (Std): -
Mounting: Floor
Insulation: 220°C
Temperature Rise: 150°C
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated - Steel
Finish: ANSI 61 Grey Finish
Dimensions: -
Weight: -

Approvals/Ratings

NRTL Listed for United States
CSA Certified
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU from Larson Electronics is a 3 Phase Energy Efficient Isolation Transformer that is powerful,

reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 28 kVA, the MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU isolation transformer is a three phase unit with a primary voltage of 400V Delta. It also provides a secondary voltage of 400V Delta. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This 60 Hz unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU general purpose transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-3P-400D-28KVA-400D-N3R-60HZ-CU achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.







Frequently Asked Questions (FAQ)