

EPS-2XPB-ESTP-2P

Explosion Proof Switch w/ E-stop - C1D1/C2D1 - (2) Stop/Start PBs (1) E-Stop PB - Double Gang Box - 2 Pole

Product ID: 310784



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPS-2XPB-ESTP-2P Explosion Proof Push Button Switch

Unit Type: Explosion Proof Push Button Switch

Dimensions: -

Voltage: 120-277V AC, 2 Pole

Horsepower: 1HP @ 120V AC / 2HP @ 250V AC

Amp Rating: 20A

Switch Style: (2) Push Buttons (Stop/Start)

Emergency Stop: (1) Mushroom Push Button - Red

Materials: Non-sparking Aluminum

Termination Options: Dead End or Feed Thru

Hub Options: 1/2" or 3/4" NPT

Ratings/Approvals

Class I, Div 1&2, Groups C,D

Class II, Div 1&2, Groups E,F,G

Class III, Div 1&2

NEMA 7 (Groups C & D)

NEMA 9 (Groups E, F, G)

Certified to USA/Canadian Standards

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPS-2XPB-ESTP-2P Explosion Proof Push Button Switch is suitable for motor and electrical control in flammable work sites. The 20-amp, 2-pole device features two, start/stop push buttons and one, emergency-stop mushroom push button. This NEMA-rated unit is constructed of non-sparking aluminum and takes on a double-gang box configuration.

The EPS-2XPB-ESTP-2P is designed for use in Class I, Divisions 1 & 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 facilities. Rated at 20 amps, this explosion proof unit accepts currents ranging between 120-277V AC. The device


features one, mushroom push button (red) which serves as an emergency stop. The unit also contains stop (red) and start (green) push buttons.

The EPS-2XPB-ESTP-2P is constructed of non-sparking aluminum and is triple coated. The entire unit is completely corrosion resistant and is NEMA rated.

Wiring/Mounting: Operators can completing wiring and mounting via a 1/2" or 3/4" NPT hub. Termination options include dead end or feed thru.


Suggested Applications: Hazardous locations, oil and gas sites, agricultural operations, grain storage, wood shops, motor control and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.









Frequently Asked Questions (FAQ)