Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ

0.5 kVA Isolation Transformer - 480V Delta Primary - 380V Delta Secondary - NEMA 3R - 50/60 Hz

Product ID: 312831



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ Isolation Transformer

Phase: Three Phase
Frequency: 50/60 Hz
Capacity: 0.5 kVA (500 VA)
Primary Voltage: 480 V Delta
Primary Current: 0.656 A
Taps: Included, 4-Position, (3) FCBN, 4.17%
Secondary Voltage: 380 V Delta
Secondary Current: 0.759 A
Winding Material: Aluminum
Insulation Class: Class B (130°C)
Temperature Rise: 80°C
Impedance (Std): 5%
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: 11.75"H x 7.00"W x 6.5"D
Weight: 18.74 lbs
Mounting: Floor or Wall Mount

Ratings

Listed for United States and Canada
ANN Cooling
NEMA 3R Rated
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ 480 V Delta 3 Phase Energy Efficient Isolation Transformer from Larson Electronics is

powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 0.5 kVA, the MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ isolation transformer is a three phase unit with a primary voltage of 480 V Delta. It also provides a secondary voltage of 380 V Delta. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor or wall mounted. The unit also features 130°C insulation with a 80°C temperature rise.

Benefits: The MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.


Safety: The MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-3P-480D-0.5KVA-380D-N3R-50.60HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


LARSON ELECTRONICS
MT-ATX-1P-208V-3KVA-120V
H1
H2
X1
X2
X3
X4
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com
WARNING
ATTENTION
General Purpose Transformer






LARSON ELECTRONICS
MT-ATX-1P-208V-3KVA-120V
Encapsulated Dry Type Transformer
Low Voltage: 208
High Voltage: 120
H1
H2
X1
X2
X3
X4
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com
WARNING
ATTENTION
General Purpose Transformer

Frequently Asked Questions (FAQ)