Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ

5.5 kVA Isolation Transformer - 3000V Wye Primary - 230V Wye x 160V Delta Secondary - NEMA 3R - Fully Potted / Encapsulated - 400 Hz

Product ID: 312832



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ Fully Potted Isolation Transformer

Phase: Three Phase
Frequency: 400 Hz
Capacity: 5.5 kVA
Vector Group: Yy0d1
Primary Voltage: 3000V Wye
Primary Current: 1.06A
Taps: N/A
Secondary Voltage: 230V Wye x 160V Delta
Secondary Current: 6.95A x 9.2A
Winding Material: Aluminum
Insulation: 220°C
Temperature Rise: 150°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: NEMA Type 3R Heavy Duty - Resin Encapsulated
Finish: ANSI 61 Grey Finish
Dimensions: 17.25" x 10.00"W x 7.75"D
Weight: 55 lb
Mounting: Wall Mount

Ratings

NRTL Listed for United States and Canada
ANN Cooling
NEMA 3R Rated
Fully Potted / Encapsulated
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ 3000V Wye 3 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 5.5 kVA, the MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ fully potted isolation transformer is a three phase unit with a primary voltage of 3000V Wye. It also provides a secondary voltage of 230V Wye and 160V Delta. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This fully potted isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated wall brackets make installation fast and easy and the offset outward facing wall installation holes allow for easy power tool access.


Safety: The MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ is an encapsulated isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-FP-3P-3000Y-5.5KVA-230Y.160D-N3R-400HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


LARSON
ELECTRONICS
DRY TYPE ISOLATION
HV/HT
BIL
LISTED
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com
DANGER – HIGH VOLTAGE
DISCONNECT POWER BEFORE OPENING DOOR
SYSTEM VOLTAGE 600V CLASS
METTRE HORS TENSION AVANT D'OUVRIR
LA PORTE
DANGER – HAUTE TENSION







Frequently Asked Questions (FAQ)