Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ETX-ISX-3P-415D-200KVA-415D-SMW-N3R

200 kVA 3PH Explosion Proof Portable Isolation Transformer, 415V Delta Primary, 415V Delta Secondary, N3R, 60 Hz/Skid Mount Wheels - ATEX Rated/EX EIIC

Product ID: 313757



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ETX-ISX-3P-415D-200KVA-415D-SMW-N3R DOE Efficiency Isolation Transformer

Transformer Type: Explosion Proof Portable Isolation Transformer
Transformer Configuration: Dry Type
Phase: Three Phase
Frequency: 60 Hz
Primary Voltage: 415V AC (15% Tolerance)
Primary Connection: Delta
Capacity: 200 KVA
Secondary Voltage: 415V AC
Secondary Connection: Delta
Knockouts: -
FCAN (Above) Taps: -
FCAN (Below) Taps: -
Tap %: TBD
Impedance: -
Efficiency @ 35% Load: -
Winding Material: Aluminum
Primary Termination (Std): Terminal Lugs
Secondary Termination (Std): Terminal Lugs
Termination Access: Front Access Cover
Mounting: Skid Mount with Wheels
Cooling: Air/Dry
Insulation: 220°C
Temperature Rise: 150°C
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 3R Heavy Duty Steel
Finish: ANSI 61 Grey
Dimensions: -

Approvals/Ratings

NRTL listed for International Locations
ATEX Rated, EX EIIC
ATEX Zones 1 and 2
NEMA 3R Indoor/Outdoor Steel Enclosure
Meets or Exceeds NEMA ST-20 Standards
Portable Isolation Transformer
Distribution Type Transformer
Built to UL-50 Standards
Seismic Qualified for Earthquake Loads
RoHS
CE Certified

Special Orders - Special Requirements

Contact us for special requirements

Weight: -
Shipping Method: Pallet Freight - LTL
Shipping Weight: 1350 lbs
Shipping Dimensions: 48"L x 40"W x 50"H

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The ETX-ISX-3P-415D-200KVA-415D-SMW-N3R Three Phase 200 KVA Explosion Proof Portable Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications in combustible sites, the ETX-ISX-3P-415D-200KVA-415D-SMW-N3R provides increased reliability and protection against critical equipment failures. This 200 KVA isolation is designed for distribution loads and potential seismic activity. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The ETX-ISX-3P-415D-200KVA-415D-SMW-N3R explosion proof portable isolation transformer is a three phase transformer with a 200 KVA capacity rating. This isolation transformer is configured with an input voltage of 415V Delta 3-Phase AC on the primary side and an output voltage of 415V Delta 3-Phase AC on the secondary side. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This ATEX-rated unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications in flammable work areas. This 200 KVA distribution transformer features 220°C insulation with a 150°C temperature rise.

Benefits: The ETX-ISX-3P-415D-200KVA-415D-SMW-N3R general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Safety: The ETX-ISX-3P-415D-200KVA-415D-SMW-N3R is an isolation transformer which means that it provides operators with an increased level of protection against electric shock and injury. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The ETX-ISX-3P-415D-200KVA-415D-SMW-N3R achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Mounting: The transformer is mounted on a cart for easy movement, transportation and positioning. The cart features four caster wheels for stability and control. The cart is also equipped with a pair of forklift skid pockets for even further versatility.

Applications: Converting local grid power for on-site equipment in combustible areas. This 200 KVA power transformer is ideal for sensitive equipment such as CNC equipment, computers, medical devices, ovens, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.




Larson Electronics
1-800-369-6671



Frequently Asked Questions (FAQ)