

MPD-DS-FM-FDS-3P-3W-5.5KV-200A-DF-BM-N3R-M1

Fused Disconnect Switch, 200 Amp, 5500V 3PH AC, 3-Pole 3-Wire, (3) Class E Time Delay Fuses, Service Rated, Floor Mount, NEMA 3R

Product ID: 314609



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-DS-FM-FDS-3P-3W-5.5KV-200A-DF-BM-N3R-M1 Disconnect Switch - Fused Disconnect

Unit Type: Service Entrance Fused Disconnect Switch
Line-In: N/A (customer provided)
Line-In Cord Cap: N/A (customer provided)
Line-In Connections: Screw Cable Lugs, Accepts Solid 14 AWG to stranded 2/0 AWG Copper or Aluminum Cable
Line-In Orientation: Sides, Top and Bottom Feed
Voltage: 5500V AC Delta or Wye
Phase: 3-Phase
Frequency: 60 Hz (60-Cycles)
Protection Method: Fused, Class E Type Fuse
Protection Type: Time Delay Fuse
Protection Fuses: (3) Fuses, Included
Protection Ampacity: 200E A
Mains Rating (Amps): 200A
Interrupting Rating: 200 kA
Horsepower (Standard): -
Horsepower (Max):
Disconnect Means: Manual via Handle
Neutral Connection: Insulated Groundable Neutral Kit with Bonding Strap
Line-Out: N/A (customer provided)
Line-Out Cord Cap: N/A (customer provided)
Line-Out Connection: Screw Cable Lugs, Accepts Solid 14 AWG to stranded 2/0 AWG Copper or Aluminum Cable
Line-Out Orientation: Sides, Top and Bottom Feed
Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door
Door: (1) Left Hinged Door w/ Pad Lockable Handle

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 891 Dead Front Switch Boards
NEMA 3R Rated for Indoor and Outdoor Use
Service Rated
Made in the USA

Auxiliary Switch: Included

Heaters: Included, Strip Type

Enclosure Material: 11GA Sheet Steel

Enclosure Finish: ANSI 49 Grey

Enclosure Type: NEMA 3R Ventilated

Mount: Floor Mount

Dimensions*: -

Weight: -

Shipping Dimensions*: 24.2"-W x 60.04"-L x 24.2"-H

Shipping Weight: 449.7 lbs

*Please note that dimensions are approximate and subject to change

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The MPD-DS-FM-FDS-3P-3W-5.5KV-200A-DF-BM-N3R-M1 from Larson Electronics is a Power Distribution Disconnect Switch that is designed for reliable, safe, and convenient power distribution at industrial work sites. This fused disconnect includes three 200-amp 5500V rated Class E fuses, Service Rated. Designed for floor mounting installations, the disconnect switch is protected by a NEMA 3R rated, steel enclosure with a ventilated design.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MPD-DS-FM-FDS-3P-3W-5.5KV-200A-DF-BM-N3R-M1 service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with three-phase 5500V AC Delta or Wye, the disconnect switch features a manual operating handle. This disconnect carries a 200 kA at 5500V AC interrupt rating and has side, top and bottom conduit entries. The switchgear comes with and accepts three 200-amp 5500V rated Class E time delay fuses. An insulated groundable neutral kit with bond strap is included for neutral connections.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power. A dead front cover protects operators from the fuses for safety. Operators can inspect the fuses through the dead front via a vented cover. Removing the dead front allows access to the fuses.

Time Delay vs. Fast Acting Fuses Two of the most common types of fuses found in power distribution equipment are time delay and fast acting fuses.

- **Time Delay:**

- **Fast Acting:**

Enclosure Design: The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI 49 grey finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor and outdoor areas.

Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.


Mount: Operators can mount the service entrance disconnect on floor.

Customization: The MPD-DS-FM-FDS-3P-3W-5.5KV-200A-DF-BM-N3R-M1 can be customized to meet specific operating and power requirements. Example of customizations include:

- Making the fused disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single pole camlock connectors for quick connections
- Adding heaters for cold environments
- Adding alarm relays for trip notification down stream
- Adding powering meters

Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.







Frequently Asked Questions (FAQ)