Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1

3.75 / 4.2 MVA Hermetically Sealed Substation Transformer, 34500V Delta Primary, 2540/4400Y/2540 x 7960/13800Y/7960 Delta x Wye Secondary - ONAN/Future ONAF, Mineral Oil, Sky Grey

Product ID: 314827



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1 Hermetically Sealed Transformer

Transformer Type: Hermetically Sealed Transformer
Transformer Configuration: Liquid Filled
Transformer Feed Type: N/A
Operation: Step-Down Operation (Not Approved for Step-Up)
Phase: Three Phase
Capacity (@ 55°C): 3.75 MVA (3,750 KVA)
Capacity (@ 65°C): 4.2 MVA (4,200 KVA)
Vector Group: Dyn1 x Dd0
Primary Voltage: 34500V
Primary Voltage Switch: N/A
Primary Voltage Class: 35 kV Class
Primary Phasor: Delta
Primary BIL: 200 KV
Secondary Voltage: 2540/4400Y/2540 x 7960/13800Y/7960
Secondary Voltage Switch: Included
Secondary Voltage Class: 15 kV Class
Secondary Phasor: Delta x Wye-N
Secondary Phasor Switch: Included
Secondary BIL: 110 KV
Frequency: 60 Hz
Temperature Rise: 55/65°C
Insulation Rating: Class A Insulation
Cooling Class: ONAN/Future ONAF
Forced Air (Fans): N/A
Provisions For Fans: Included, Future Fan Cooling, 5.25 MVA (@ 65°C Rise)

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.29
Complies with ANSI / IEEE C57 12.34
Complies with ANSI / IEEE C37.47
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.110
Complies with ANSI / IEEE C57.12.131
Complies with ANSI / IEEE C62.11
Complies with ANSI / IEEE C62.22
Complies with ANSI / IEEE 386
Complies with NEMA 260-1996
Complies with ANSI / IEEE C2
Complies with ANSI Z535.4
Complies with ASTM D3487
Complies with 10 CFR Part 431
Complies with ASTM D6871
Complies with CSA C88
Complies with CSA C88.1
Complies with CSA C802-3
Complies with CSA C2.1-06
Complies with CSA C88-16

Cooling Radiator: Included, Panel Type, Has Upper And Lower Drain Plugs, ANSI #70 Sky Grey
H.V Tap Changer: 5-Position De-energized Tap Changer (DETC)
H.V Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps
H.V Tap %: 2.5%
H.V Tap Changer Switch Rating: 35 KV
H.V Tap Changer Switch Location: H.V Side, Top Mounted
Impedance: 6.79%
Primary Connection Type: Live Front
Primary Termination Arrangement: Inline, Top Mounted
Primary Termination: NEMA 4-Hole Pad connectors
Primary Bushing Qty: (3)
Primary Bushing Rating: 35 KV Class, 200 KV BIL, 600A, Dead Break, Porcelain, ANSI #70 Sky Grey
Primary Neutral Connection: N/A
Primary Surge Arrestors: Included, (3) Metal Oxide Polymer Housed Station Class
Primary Surge Arrestor Voltage Rating: 36 KV
Primary Surge Arrestor MCOV Rating: 29 KV
Primary Over Current Protection (OCP): N/A
Primary Over Current Protection (OCP): N/A
Primary Over Current Protection Method: N/A
Primary Over Current Protection Holder: N/A
Primary Bushing CT: Included, (1) Per Each Phase, 600:5 Ratio MR, C400 Accuracy Class
Primary Grounding Provisions: N/A
Secondary Connection Type: Live Front
Secondary Termination Arrangement: Inline, Top Mounted Enclosed in ATC
Secondary Termination: NEMA 4-Hole Pad connectors
Secondary Bushing Qty: (4)
Secondary Bushing Rating: 15 KV Class, 110 KV BIL, Porcelain, ANSI #70 Sky Grey
Secondary Neutral Connection: Included
Secondary Bushing CT: Included, (2) Per Each Phase; (1200:5 Ratio MR, C400 Accuracy Class) & (1200:600 Ratio, 0.3-B1.8 Metering Accuracy)
Secondary Surge Arrestors: Included, (3) Metal Oxide Polymer Housed Station Class
Secondary Surge Arrestor Voltage Rating: 15 KV
Secondary Surge Arrestor MCOV Rating: 12.7 KV
Secondary Grounding Provisions: Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Connection To 2/0 to 500 KCMIL Stranded Copper conductor
Secondary Neutral Bushing CT: Included, (1) 600:5 Ratio MR, C400 Accuracy Class
Metering Current Transformer (CT): Included
Metering Panel: Included
Auxiliary Control Panel: : N/A
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Rating: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Mineral Oil Fluid, Non-PCB Fluid
Fluid (Oil) Capacity*: TBD
Fluid (Oil) Weight*: TBD
Liquid Level Indicator: Included
Winding Temperature Indicator: Included Thermometer
Liquid Temperature Indicator: Included Thermometer
Pressure/Vacuum Indicator: Included, With Scale Range Of Plus Or Minus 10 PSI
Rapid Rise Relay: Included, (63) Qualitrol 910-013-03
Pressure Relief Device: Included, Cover mounted
Nitrogen Oil Preservation System: Included With A Nitrogen Tank And All Necessary Accessories
Pressure Reducer: Included, Three-Stage
Gas Relay: Included
Fault Indicator: Included, Buchholz Relay
Gas Sampler Valve: N/A
Fill Valve: Included
Fill Valve Location: Top Mounted, 1 inch
Drain Valve: Included (1 inch) W/ Sampling Port
Drain Valve Location:

Complies with CSA C802.1
Complies with CSA C50
Complies with CSA C227.5
Complies with CSA C227.4

Features
Hot Stick Included, HV Door Mount
Penta-head Bolt Entry Assembly
High-Fire Point Insulating Fluid
Non-PCB Insulating Fluid
Tamper Proof Housing
Hinged Front Compartment Doors, Pad Lockable
NEMA 3R Wiring Compartment

Efficiency %: TBD

Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 75°C Reference Temp.
Off-Load Loss (in watts): TBD
On-Load Loss (in watts): TBD
Total Load Loss (in watts) at 100%: TBD

Total Losses at 55°C LL Temp.& 20°C NL Temp.

Total Load Loss (in watts) at 50%: TBD
Note: Losses offered are typical only, not guaranteed

Labeling:
Externally Stenciled (Painted) KVA Rating
Externally Stenciled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

Factory Tests:
Winding Resistance Test
Insulation Resistance Test
Voltage Ratio Error Test
Pressure Integrity Test
Short-circuit Impedance Test
Separate Source Voltage Withstand Test
No-load Loss (Wattage) Test
Induced Voltage Withstand Test
Load Loss (Wattage) Test
Leak Test

Shipping:
Shipped on pallet on open flatbed

Winding Material: Copper
Ambient Temperature Rating: 40°C
Ambient Operating Temperature Range: -40°C to +45°C
Sound Level: Complies With NEMA TR-1
Elevation (Altitude): 3300ft (1000 meters) Above Sea Level
Core Material: Silicon Steel, Grain Oriented
Tank Material: Steel
Cabinet Material: Steel
Base Platform Material: Steel
Hardware Material: Stainless Steel
Portability: Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
Housing Type: Metal Casing Liquid Filled Transformer
Enclosure Rating: NEMA 3R Weatherproof
Seismic Rating: N/A
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: ANSI #70 Sky Grey
Mounting: Supporting Structures
Conduit Opening: N/A
Tank Cover Access Handhole: Included
Dimensions*: 185”L x 159”W x 161”H
Weight*: 89,560 Lbs
*Please note that numbers are approximate and subject to change

Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1 Hermetically Sealed Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in outdoor locations. The low operating costs, low heat emissions, and low cost of ownership make this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The substation transformer should be installed on supporting structures.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The industrial transformer features a primary voltage of three-phase 34500V Delta and a secondary voltage of three-phase 2540/4400Y/2540 x 7960/13800Y/7960 Delta/Wye. This system is rated for 3.75 MVA (3,750 KVA). We offer systems with loop or radial feed, as well as dead front or live front primary connections. The transformer features a 5-position off-load tap changer with two, + 2.5% taps above and two, + 2.5% taps below to allow small changes for voltage. There is a rapid rise relay present on the system. The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops). The MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1 doesn't have fans but has mounting provisions for future fans.

Temperature Rise: This unit features 55/65°C temperature rise for reduced heat waste, increased reliability and longer life. At 55°C temperature rise, the transformer offers 3.75 MVA (3,750 KVA). At 65°C temperature rise, the transformer offers 4.2 MVA (4,200 KVA). The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in outdoor areas.

Insulation Fluid: The MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1 features mineral oil fluid (ONAN). We offer transformers with biodegradable fluid or FR-3 fluids, if needed.

Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to

120% load conditions, which helps preserve the transformer's lifespan and performance.
Gauges: The following gauges are included with the system: liquid level indicator, Fluid temperature indicator, Winding Temperature Indicator, pressure/vacuum indicator. Standard liquid level, temperature and pressure/vacuum gauges are analog dial types.
Fault Pressure Devices: There is a Buchholz relay fault indicator on this unit.
Gas Relay: A gas relay with indicators for light gas and heavy gas is included with the transformer. The relay includes two Dry Type Form C auxiliary contacts (1NO + 1NC) for remote alarm when pressure rises above in-field set pressure located in auxiliary control cabinet.
Surge arresters: This system comes with surge arresters on both the primary and secondary sides.
Load Break Switch: The transformer is not equipped with a load break switch.
Valves: The MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1 is equipped with a pressure relief valve.
Protection Fuses: This transformer contains bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.
Mount: This hermetically sealed transformer is equipped with a skid type base with lifting lugs.
Benefits: The MT-PSTH-R7-3P-DMA-3.75MVA-D.YMP.VF-HT-LNT-A6-CMP-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


OFF
ON
NON-PCBs
OFF
ON
#262857
CAUTION
HIGH VOLTAGE
CAUTION
HIGH VOLTAGE


CAUTION
HIGH VOLTAGE

Frequently Asked Questions (FAQ)