Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-SS-FP-1P-208.240V-25KVA-120.208.240V-N4X-ES

25 kVA Isolation Transformer - 208x240V Primary - 120x208x240V Secondary - Stainless Steel - NEMA 4X - IP66 - Shielded

Product ID: 315603



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-SS-FP-1P-208.240V-25KVA-120.208.240V-N4X-ES Fully Potted Isolation Transformer

Phase: Single Phase
Frequency: 60 Hz
Capacity: 25 KVA
Primary Voltage: 208x240 V
Primary Connection: Parallel x Series (Vx2V)
Primary FCAN (Std): 2 x 2.5%
Primary FCBN (Std): 4 x 2.5%
Secondary Voltage: 120x208x240 V
Secondary Connection: Parallel/Series-N (V/2V)
Winding Material: Copper
Efficiency Regulation: No Efficiency Specification
Insulation: 180°
Temperature Rise: 115°C
Primary Termination (Std): Mechanical Lugs
Secondary Termination (Std): Mechanical Lugs
Electrostatic Shield (Including Core and Coils): One-foil type, located between primary and secondary windings is missing
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 4X Stainless Steel 316 - Resin Encapsulated
Finish: Stainless Steel 316 Polished
Dimensions: 21.89"H x 15.75"W x 14.13"D
Weight: 385 lb
Mounting: Floor

Ratings

NRTL Listed for United States and Canada
Stainless Steel Enclosure
Dry Type Cooling
NEMA 4X Rated
Fully Potted / Encapsulated
Electrostatically Shielded

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-SS-FP-1P-208.240V-25KVA-120.208.240V-N4X-ES 240 V 1

Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-SS-FP-1P-208.240V-25KVA-120.208.240V-N4X-ES provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 25 kVA, the MT-ISX-SS-FP-1P-208.240V-25KVA-120.208.240V-N4X-ES transformer is a single phase unit with a primary voltage of 208x240 V. It also provides a secondary voltage of 120x208x240 V. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The stainless steel Type 4X enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 180° insulation, a 115°C temperature rise, and is rated IP66.

Benefits: The MT-ISX-SS-FP-1P-208.240V-25KVA-120.208.240V-N4X-ES general purpose transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This fully potted transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


H1
H2
7 5 3 1
2 4 6 8
X4
X2
X3
X1
LARSON
ELECTRONICS
MT-ATX-SS-FP-1P-480V-25KVA-120.240V-N4X
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com



Frequently Asked Questions (FAQ)