Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1

50 KVA Overhead Distribution Transformer, Pole Mount, 12000Y/6930 Grounded Wye Primary, 120/240V Secondary, Mineral Oil, Copper, ONAN, W/ Tap Changer, Light Grey

Product ID: 316702



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1 Pole Mount Overhead Transformer

Transformer Type: Overhead Distribution Transformer, Conventional Type
Transformer Configuration: Liquid Filled Pole Mounted
Transformer Polarity Type: Subtractive
Phase: Single Phase
Capacity: 50 KVA
Primary Voltage: 12000Y/6930
Primary Voltage Switch: N/A
Primary Voltage Class: 15 kV Class
Primary Phasor: Grounded Wye
Primary BIL: 95 kV
Secondary Voltage: 120/240V (L-N-L)
Secondary Voltage Class: 1.2 kV Class
Secondary Phasor: Dual Windings, Single Phase
Secondary BIL: 30 KV
Frequency: 60 Hz
Temperature Rise: 65°C
Insulation Rating: Class E Insulation - 120°C, 248°F
Forced Air (Fans): None
Cooling Class: ONAN; Self-Cooled
Tap Changer: 5-Position Tap Changer
Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps
Tap %: 2.50%
Tap Changer Switch Location: HV Side
Impedance: 1.0-4.5% Typical, 2.0%Target
Primary Connection Type: Live Bushing Lug
Primary Termination: Cover Mount Porcelain High Voltage Bushings w/ Eyebolt Lug

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Complies with ANSI / IEEE #C57.12.00
Complies with ANSI / IEEE #C57.12.20
Complies with ANSI / IEEE #C57.12.28
Complies with ANSI / IEEE #C57.12.31
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.80
Complies with ASTM D3487
Non-PCB Insulating Fluid
Lifting Lugs Included

Efficiency: 98.90%
Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 85°C Reference Temp.
No Load Loss (in watts): +/- 176W
Full Load Loss (in watts): +/- 650W
Total Load Loss (in watts): +/- 826W

Note: Losses offered are typical only, not guaranteed

Primary Bushing Material: Plated to Accommodate Aluminum/Copper

Primary Bushing Color: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)

Primary Terminal Size: 5/16" Terminal Opening For Conductor Size #8 Solid - #2 Stranded

Primary Connection Qty: (2)

Primary Lightning Arrestors: N/A

Primary Lightning Mounting Provision: Mounting Provisions for Installing Lightning Arrestors on H1 and H2 Primary Terminals

Primary Lightning Arrestors Voltage Rating: N/A

Primary Lightning Arrestors MCOV Rating: N/A

Secondary Connection Type: Sidewall Mounted Polymer Terminals

Secondary Connection Material: Plated to Accommodate Aluminum/Copper

Primary Terminal Size: 5/16" Terminal Opening For Conductor Size #8 Solid - #2 Stranded

Secondary Connections: Eyebolt Lugs

Secondary Connection Qty: (3)

Secondary Neutral Connection: Secondary X2 Neutral Grounded to Tank via 1/2”-13 UNC Tapped Hole, 7/16” Deep Bung & Copper Ground Strap

Terminals: Tin Plated Primary and Secondary - Accepts Copper or Aluminum Connections

Grounding Provisions: (1) 1/2”-13 UNC Tapped Lug w/ Grounding Strap under X2 Bushing, (1) Cover Band to Tank Ground 1/2”-13 UNC Tapped Lug, (1) Tank Grounding Lug on Side of Tank

Transformer Protection: N/A

Load Break Switch: N/A

Efficiency Standard(s): Meets DOE 2016 10CFR Part 431 Standard, Meets ANSI/IEEE Standards

K-Factor Rating (Harmonic Mitigation): K-1 (Standard)

Pulse Drive Rating: N/A

Insulation Fluid: Mineral Oil, Non PCB Fluid

Fluid Capacity*: 15.16 Gallons

Fluid Weight*: 136.68 lbs

Liquid Level Indicator: Internal In-Tank Oil Level Line

Temperature Indicator: N/A

Pressure/Vacuum Indicator: N/A

Pressure Relief Device: Included, Automatic Action

Fault Indicator: N/A

Oil Level Marking: Internal

Fill Valve: N/A (Tank Filled via Removable Lid)

Drain Valve: 1/2" NPT Port w/ Removable Bolt

Winding Material: Copper

Ambient Temperature : -26.7°C to 41.1°C

Average Humidity: 88% (Summer) / 66% (Winter)

Sound Level: 48 dBA, Comply with NEMA TR-1 and ANSI/IEEE C57.12.90

Elevation Level: 4789ft above Sea Level

Core Material: Grain Oriented Steel

Tank Material: Coated Steel

Housing Material: Coated Steel w/ Corrosion Resistant Cover Band, Removable Top Cover

Hardware Material: Stainless Steel Hardware

Bird Gaurd: Included, For Bushing and Arreters

Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating, Meets or Exceeds IEEE C57.12.31

Finish Color: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)

Mounting: Double Hanger Bracket

Mounting: Pole Mount via Hangar Brackets

Lifting Lugs: Included

Dimensions*: 24.8"-W x 26.77"-D x 40.16"-H

Tank Diameter*: 20.47" OD

Dry Weight*: 374.78 lbs

Total Weight (Liquid Filled)*: 605 lbs

*Please note that numbers are approximate and subject to change

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1 Overhead Distribution Pole Mounted Transformer from Larson Electronics offers powerful, reliable and efficient power distribution in outdoor and public locations. The low operating costs, low heat emissions and low cost of ownership makes this transformer ideal for a wide range of applications

and businesses. This power distribution system is designed for overhead, pole mount installations and use.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 50 KVA, the industrial transformer features a primary voltage of 12000Y/6930 Grounded Wye and a secondary voltage of single-phase 120/240V (L-N-L). This transformer connects to a three phase electrical grid system to provide single phase low voltage power for indoor distribution. This pole mount transformer features porcelain high-voltage, dual bushings on the primary side and three bushings on the secondary side. Equipped with copper windings and a grain oriented steel core, this overhead distribution transformer consists of one coil and two core loops. Tin plated terminals on the primary and secondary side accepts copper or aluminum connections.

The MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1 is air cooled and does not have fans or mounting provision for fans. This unit features a 65°C temperature rise for reduced heat waste, increased reliability and longer life. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Insulation Fluid: The MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1 features mineral oil insulation fluid. Internal marking is available for proper oil level monitoring. We offer transformers with FR-3 oil fluid, if needed.

Gauges: There are no gauges on this transformer. We can add liquid level, temperature and pressure/vacuum gauges at an additional cost. Standard liquid level, temperature and pressure/vacuum gauges are analog, manual reading types.

Pressure Relief Device: An automatic pressure relief device is included with this transformer.

Rapid Rise Relay: There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.

Surge arresters: This system is not equipped with lightning arresters. Mounting provisions for installing customer provided lightning arrestors on the H1 and H2 primary terminals are included for installing arresters in-field.

Valves: The MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1 is not equipped with fill or drain valves. The transformer can be filled via removing the top lid. A drain port w/ bolt plug is equipped.

Protection Fuses: This transformer does not contain fuses or circuit breakers. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.

Mount: The heavy-duty enclosure makes the unit suitable for outdoor applications. Equipped with hanger brackets and lifting lugs, this overhead power distribution system can be mounted on poles.

Benefits: The MT-UPM-R7-1P-GMT-50KVA-SLZ-BB-A6-BM-CZ-1ZZ-M1 heavy-duty transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

We offer completely self protected (CSP) pole mount overhead transformers at an additional cost.

Applications: General purposes, industrial sites, electrical rooms, public locations, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, public locations and more. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units

almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


MISTER




100
LARSON
ELECTRONICS


WARNING

Frequently Asked Questions (FAQ)