

MT-DOE16-1P-480V-15KVA-120.240V-PM-NE

15 kVA Isolation Transformer - 480V Primary - 120/240V Secondary - Single Phase - Pipe Mount, No Enclosure

Product ID: 320508



Image: MT-DOE16-1P-480V-15KVA-120.240V-PM-NE

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-1P-480V-15KVA-120.240V-PM-NE-N3R Isolation Transformer

Phase: Single Phase
Frequency: 60 Hz
kVA: 15
Primary Voltage: 480 V
Taps: 2 x 2.5% FCAN; 4 x 2.5% FCBN
Secondary Voltage: 120/240 V
Winding Material: Aluminum
Insulation: 220°C
Temperature Rise: 150°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: No Enclosure
Finish: -
Dimensions: -
Weight: -
Mounting: Steel Pipe Mount, 4' from the Ground

Ratings

Listed for United States and Canada
ANN Cooling
Isolation Transformer
No Enclosure

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-DOE16-1P-480V-15KVA-120.240V-PM-NE 480 V 1 Phase Energy Efficient Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. The MT-DOE16-1P-480V-15KVA-120.240V-PM-NE provides

increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. This transformer does not have an enclosure.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Transformer Features: With a transformer rating of 15 kVA, the MT-DOE16-1P-480V-15KVA-120.240V-PM-NE isolation transformer is a single phase unit with a primary voltage of 480 V. It also provides a secondary voltage of 120/240 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. This transformer is designed to be mounted to steel pipes, 4' from the ground. The unit also features 220°C insulation with a 150°C temperature rise.

Benefits: The MT-DOE16-1P-480V-15KVA-120.240V-PM-NE isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Safety: The MT-DOE16-1P-480V-15KVA-120.240V-PM-NE is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-1P-480V-15KVA-120.240V-PM-NE achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671




www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Frequently Asked Questions (FAQ)

There are no Faqs