

**MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU**

**50 kVA Isolation Transformer - 4160V Primary - 240V Secondary - NEMA 4X - Stainless - Single Phase - Fully Potted / Encapsulated - Copper**

**Product ID: 320700**



Image: MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU Fully Potted Isolation Transformer**

**Phase:** Single Phase  
**Frequency:** 60 Hz  
**Capacity:** 50 KVA  
**Primary Voltage:** 4160 V  
**Primary BIL:** 10 kV  
**Primary FCAN:** TBD  
**Primary FCBN:** TBD  
**Secondary Voltage:** 240 V  
**Secondary BIL:** 10 kV  
**Winding Material:** Copper  
**Efficiency:** DOE 2016 / NRCAN 2019 (Also Meets ON Reg. 404/12)  
**Insulation:** 220°C  
**Temperature Rise:** 150°C  
**Impedance (Std):** -  
**Seismic Zone:** Zone 4  
**Sound Level:** Meets NEMA ST-20 Standards  
**Primary Termination:** -  
**Secondary Termination:** -  
**Enclosure Material:** NEMA Type 4X - 304 Stainless Steel  
**Finish:** 304 Stainless Steel  
**Dimensions:** TBD  
**Weight:** TBD  
**Mounting:** Floor

**Ratings**

NRTL Listed for United States and Canada  
ANN Cooling  
NEMA 4X Rated  
Isolation Transformer  
Fully Potted / Encapsulated

**Special Orders - Special Requirements**

Contact us for special requirements  
**Toll Free:** 1-800-369-6671  
**Intl:** 1-903-270-1187  
**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

The MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU 50 KVA 1 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU features a NEMA 4X rated stainless steel enclosure.

**\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\***

**Transformer Features:** With a transformer rating of 50 kVA, the MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU isolation transformer is a single phase unit with a primary voltage of 4160 V. It also provides a secondary voltage of 240 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The stainless steel NEMA Type 4X enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor-mounted. The unit also features 220°C insulation with a 150°C temperature rise.

**Benefits:** The MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material helps to improve performance. The close tolerances used during manufacturing also eliminate burrs, which hinder performance. Each core is specially coated to prevent the ingress of moisture and is electrically balanced to minimize axial forces during short-circuit situations.

This fully potted isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

**Safety:** The MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU is an encapsulated isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-SS-FP-1P-4160V-50KVA-240V-N4X-CU achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

**Applications:** General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or



[sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) to discuss your specific requirements.

Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664





---

## Frequently Asked Questions (FAQ)

There are no Faqs