Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

VFD-3P-400.480V-1.5HP-400.460V-DCM

1.5 HP Variable Frequency Device - 400/480V AC 3PH Input - 0-400/460V AC 3PH Output - 3.4 Amps - 1.1 kW

Product ID: 320747



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

VFD-3P-400.480-1.5HP-400.460V-DCM Variable Frequency Device

Unit Type: 3 Phase Delta, 3 Wire Variable Frequency Device
Dimensions: 7.24" x 3.85" x 5.31"
Weight: 4.4 lbs
Input Voltage: 400/480V AC, 3PH
Input Current: 4.0/3.6 Amps
Input Frequency: 50/60 Hz
Output Voltage: 0-400/460V AC, 3PH
Output Current: 3.4/3.0 Amps
Output Frequency: 0 to 240 Hz
Kilowatts: 1.1 kw
HP: 1.5
Starting Torque: 1 Hz/150%
Carrier Frequency: 1.0-16kHz, auto adjusted according to temperature and load
Frequency Accuracy: Digital setting: 0.01Hz, Analog Setting: Max frequency X 0.05%
Torque boost: Automatic torque boost; manual torque boost: 0.1%~30.0%
V/f curve: Linear, multiple point and square type (1.2 power, 1.4 power, 1.6 power, 1.8 power, square)
Inputs: 7 on-off programmable digital, 1 high-speed pulse, 2 programmable analog (AI1: 0~10V or 0/4~20mA A12: 0~10V or 0/4~20mA)
Outputs: 1 programmable open collector, 1 analog (open collector or high-speed pulse), 2 relay, 2 analog (0/4~20mA or 0~10V)
Analog Input/Output: 2 Input (0~10V or 0/4~20mA), 2 Output (0/4~20mA or 0~10V)
Communication Terminal: RS485 communication interface, support MODBUS-RTU communication protocol
Overload: 150% @ 60s, 180% @ 10s, 200% @ 3s

Features/Ratings

Automatic Voltage Regulation
LED Display
3 Phase Delta, 3-Wire Configuration

Operating Temp: –10°C to +40°C
Max Operating Humidity: 90% (non condensing)
Materials: -
Mounting: Surface
Color: Grey

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The VFD-3P-400.480V-1.5HP-400.460V-DCM from Larson Electronics is a 3 Phase, 3-Wire Configuration Variable Frequency Drive that is suitable for improving AC motor performance in industrial operations. This fan-cooled unit features a three-phase 400/480V AC input and three-phase 0-400/460V AC output voltage comparability. Designed for steady speed error, fast torque rise and protection from resonance vibrations, the device provides an output current of 3.4 amps and an operating frequency range of 0 to 240 Hz with 1.5 horsepower.

The VFD-3P-400.480V-1.5HP-400.460V-DCM offers accurate AC motor control in industrial facilities. This 1.1 kw unit is compatible with three-phase nominal 400/480V AC input and three-phase 0-400/460V AC output voltage, provides an output current of 3.4 amps and an operating frequency range of 0 to 240 Hz. This device supports seven on-off programmable digital inputs, one high-speed pulse input and two programmable analog inputs, as well as one programmable open collector output, one analog output (open collector or high-speed pulse), two relay outputs and two analog outputs. The device also features a total of four operating modes: Keypad control, Terminal control, Serial communication control, and Frequency Setting Mode for digital setting, analog setting, pulse frequency setting, serial communication setting, multi-step speed setting & simple PLC, PID setting, etc.

The VFD-3P-400.480V-1.5HP-400.460V-DCM is designed for indoor applications and operating temperatures ranging between –10°C to +40°C. Operators may mount the variable frequency drive on compatible surfaces. This device measures 7.24" x 3.85" x 5.31" and weighs approximately 4.4 lbs.

Applications: Speed control of AC motors, industrial machines, large compressors, energy savings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.


FWD
REV
ALM
Hz
A
V
MENU
ESC
ENTER
DATA
FWD
JOG
REV
STOP
RESET
WARNING Risk of electric shock
Read the manual and follow the safety instructions before operation.
Do not remove the cover while power is applied.
Wait for 10 minutes after disconnecting power supply to open the cover.
Do not connect power to output terminals.
Must securely ground (earth) the inverter.


FWD
REV
ALM
Hz
A
V
MENU
ESC
FWD
JOG
REV
STOP
RESET
MISTER
A34
WARNING Risk of electric shock


A34
MISTER
Approved


+85°C
VENT
400V22µF
400V22µF
6N
6N

Frequently Asked Questions (FAQ)