

MT-CPT-7980V-2KVA-120V

2 KVA Control Power Transformer - 7980V Input Voltage - 120V Output Voltage

Product ID: 320953



Image: MT-CPT-7980V-2KVA-120V

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-CPT-7980V-2KVA-120V Control Power Transformer

Transformer Type: Control Power Transformer

Transformer Configuration: Dry Type

Phase: Single Phase

Frequency: 60 Hz

Capacity: 2 kVA (2000 VA)

Primary Voltage: 7980 V

Primary Coil Configuration: Vacuum Encapsulated In Epoxy To Seal Out Moisture And Contaminates, And To Provide A Higher Ability To Withstand Short-Circuit Forces Than Conventional Dry Type Transformers

Primary BIL: 95 KV

Secondary Voltage: 120 V

Material: Copper

Primary Termination: 1/4"-20 brass screws

Primary Tap Termination: 1/4"-20 brass screws or #10 brass screws depending on the design selected, and are supplied with a copper link

Tap Changer: 3-Position Tap Changer

Tap Qty: (1) FCAN Above Taps, (1) FCBN Below Taps

Tap %: 7.50%

Secondary Termination: 1/2"-13 brass bolts supplied with series/parallel copper links

Insulation: 130°C

Temperature Rise: 55°C

Lifting Provisions: Included, (2) holes, Ø1.12

Frame Material: Zinc Plated Steel

Mounting: Heavy Steel Feet

Dimensions: 17"-L, 9.5"-H

Weight: 130 Lbs

Approvals/Ratings

Control Power Transformer

UL Listed

NRTL Listed for United States and Canada

NRTL Certified to CSA 22.2 NO 66.1

NRTL Certified to CSA 22.2 NO 66.2

NRTL Certified to UL 5085-1

NRTL Certified to 5085-2

Tests

Meets all dielectric test requirements of IEEE 57.13

Includes full-wave and chopped-wave impulse tests

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail:

The MT-CPT-7980V-2KVA-120V from Larson Electronics is a 2 kVA Single Phase Control Power Transformer that is completely dry-type transformer cast in epoxy, powerful, reliable, and innovatively designed. With high-quality silicon steel laminations providing optimal performance, the MT-CPT-7980V-2KVA-120V provides increased reliability and protection against critical equipment failures. This control power transformer features an innovative design with a unique terminal block design that allows for a quick and easy hookup along with the ability to easily install fuse clips to the unit. The uniquely designed molded coil covers give this control transformer superior cooling abilities and a sleek appearance.

Transformer Features: With a transformer rating of 2 kVA (2000 VA), the MT-CPT-7980V-2KVA-120V is a machine tool industrial single phase control power transformer with primary voltages of 7980V. It also provides secondary voltage of 120V. Featuring compact and innovative construction, this unit's cores are manufactured with high-quality silicon steel laminations using state of the art technology.

This unit boasts an innovative terminal block design that allows for easy hookup. Connecting this unit is a simple task thanks to the terminal connection numbers being molded into the terminal block which corresponds to the nameplate and wiring diagrams. A unique fin-shaped, injection molded coil cover gives this unit superior cooling abilities. The unit also features a 130°C insulation class with a 80°C temperature rise.

Benefits: The MT-CPT-7980V-2KVA-120V control power transformer offers many benefits to the consumer. Full encapsulation of the windings and internal terminations ensures that the unit is protected from moisture, dirt, dust and other contaminants. Removeable finger safe terminal covers contribute towards the overall clean and sleek look of the unit. The compact and innovative design features make this a great choice for industrial tool applications.

This control transformer has heavy steel mounting feet that are either welded or bolted to the core. This transformer features terminal block terminations.

Applications: The CPT Transformer is an indoor, self-cooled, single-phase, dry-type control power transformer designed to provide control power in medium voltage switchgear. Nominal primary voltages range from 2.4 kV to 14.4 kV at 60 Hertz. Secondary voltages are configured for series/parallel operation at 120 V or 240 V

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)

There are no Faqs