Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## MPD-MES-VFI-3P3W-11-23KV-600A-BE-FM-MET-CU-N3R-M1

# Metal Enclosed Switchgear, 600 Amp, 23 KV AC, 3-Pole 3-Wire, 1 IN 1 OUT, Floor Mount, Bottom Entry, Copper Bus, NEMA 3R

**Product ID: 322657**



Image: MPD-MES-VFI-3P3W-11-23KV-600A-BE-FM-MET-CU-N3R-M1

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MPD-MES-VFI-3P3W-11-23KV-600A-BE-FM-MET-CU-N3R-M1 Metal Enclosed Switchgear -Vacuum Fault Interrupter Switch**

**Unit Type:** Metal Enclosed Switchgear - Vacuum Fault Interrupter Switch
**Line-In Connections:** Terminal Lugs, Accepts 750MCM-1/0
**Line-In Orientation:** Bottom Feed
**Maximum Design Voltage:** 23 KV AC, 3 Phase
**Voltage BIL:** 125 KV
**Momentary Current, 10 Cycles (Sym.):** 12.5 kA
**3-Second Withstand Current (Sym.):** 12.5 kA
**Configuration:** 3-Pole, 3-Wire
**Fault Interrupter Continuous Current:** 600 A
**Fault Interrupter Interrupting Current (Sym./Asym.):** 12.5/20 kA
**Fault Interrupter Making Current (Sym.):** 12.5 kA
**Fault Interrupter Cable Charging Interrupting Current:** 25 A
**Protection Method:** Vacuum Fault Interrupter Switch
**Fuse with Switch Uni-Rupter Cont. Rating:** N/A
**Fuse with Switch Uni-Rupter Suppression Loading:** N/A
**Fuse Holder Rating:** N/A
**Spare Fuses:** N/A
**Disconnect Means:** Manual via Handle
**Incomers:** (1) 600 VFI

**Ratings**

NRTL Listed Service Equipment
NRTL Listed to UL 891 Dead Front Switchboards
NEMA 3R Rated for Indoor and Outdoor Use
Made in the USA

**Outgoings:** (1) 600 VFI

**Bus Material:** Copper

**Metering Current & Potential Transformer (CT/PT):** Included Mount and Termination CT/PT

**Line-Out Connection:** Terminal Lugs, Accepts 750MCM-1/0

**Line-Out Orientation:** Bottom Feed

**Form Factor:** Rectangular, Slim-profile Enclosure w/ Lockable Door, 1 incoming panel, 1 outgoing panel

**Panel Configuration:** 2 x Non-Fused Compartments

**Housing Type:** Compartmental Air-Filled Cabinet, (1) Front Left Hinged Door w/ Pad Lockable Handle and (1) Rear Right Hinged Door w/ Pad Lockable Handle, Fuse Door and Switch handle are Kirk Key Interlocked

**Enclosure Material:** #12GA Sheet Steel

**Enclosure Finish:** Munsell Bell Green

**Enclosure Type:** NEMA 3R Ventilated, internal thermostatically controlled 250W, 120VAC heaters to prevent condensation in the enclosure, Automation control includes a 120VAC to 24VDC power supply capable of powering the entire control. A battery charger is provided and utilize 120VAC from the internal CPTs

**Mount:** Floor/Pad Mount

**Dimensions:** 54.75"-W x 62.625"-L x 50"-H

**Weight:** TBD

**Shipping Dimensions:** TBD

**Shipping Weight:** TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

**Special Orders - Special Requirements**

Contact us for special requirements
**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**Fax:** 1-903-765-7664
**E-mail:** sales@larsonelectronics.com

*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250*

**Made in the USA**

**The Larson Electronics MPD-MES-VFI-3P3W-11-23KV-600A-BE-FM-MET-CU-N3R-M1 Metal Enclosed Switchgear is designed for reliable, safe and convenient power distribution at industrial work sites. Designed for floor mounting installations. This bottom feed switchgear is protected by a NEMA 3R rated, steel enclosure with a ventilated design.**

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

The MPD-MES-VFI-3P3W-11-23KV-600A-BE-FM-MET-CU-N3R-M1 service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with 23KV AC, the switchgear features a manual operating handle. This bottom feed disconnect carries a 12.5 kA at 23KV AC interrupt rating. The switchgear comes with and accepts vacuum fault interrupter switches.

**Operation:** The switchgear features front control panel and rear termination equipped with a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power and bur bars (at rear). A dead front cover protects operators from the switches for safety. Operators can inspect the fuses through the dead front via a vented cover. Removing the dead front allows access to the switches.

**Time Delay vs. Fast Acting Fuses** Two of the most common types of fuses found in power distribution equipment are time delay and fast acting fuses.

> **Time Delay:** Time delay fuses are tripped once overcurrent heat builds up enough to melt the fuse element over a period of time. That period of time varies between different time delay fuses depending on the application. Time delay fuses decrease the chances of false tripping. During startup, many components require a large current for a very short amount of time. In other words, a time delay fuse disconnects the circuit only when the overcurrent persists in the line.
>
> **Fast Acting:** Fast acting fuses are tripped immediately upon sensing an overcurrent or short circuit in the line. They are ideal for electronics, components, or systems that cannot withstand sudden changes in current. A fast acting fuse will not withstand a temporary overload such as one that occurs during the startup process.

**Enclosure Design:** The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI green finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor and outdoor areas.

**Certification:** This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

**Mount:** Operators can mount the service entrance disconnect on floors and flat surfaces.

**Customization:** The MPD-MES-VFI-3P3W-11-23KV-600A-BE-FM-MET-CU-N3R-M1 can be customized to meet specific operating and power requirements. Example of customizations include:

• Making the fused disconnect portable and certified to NRTL UL 1640 for portable equipment

• Adding single pole camlock connectors for quick connections

• Adding heaters for cold environments

• Aiding alarm relays for trip notification downstream

• Adding power meters

**Applications:** This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, solar equipment, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

There are no Faqs