

MPD-DS-FM-NFDS-3P-4W-34.5KV-4000A-DF-BM-N3R-GO-VB-M1

MV Disconnect Switch, 4000 Amp, 34.5KV 3PH AC, 3-Pole 4-Wire, Floor Mount, NEMA 3R, Group-operated, Vertical Break Air Switch

Product ID: 324701



Image: MPD-DS-FM-NFDS-3P-4W-34.5KV-4000A-DF-BM-N3R-GO-VB-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-DS-FM-NFDS-3P-4W-34.5KV-4000A-DF-BM-N3R-GO-VB-M1 Disconnect Switch - Non-Fused Disconnect

Unit Type: Service Entrance Non-Fused Air Disconnect Switch, Vertical Break

Line-In: N/A (customer provided)

Line-In Cord Cap: N/A (customer provided)

Line-In Connections: Terminal Lugs, Accepts 750MCM-1/0

Line-In Orientation: Bottom Feed

Nominal Voltage: 34.5KV AC Delta or Wye

Rated Voltage: 35KV

Phase: 3-Phase

Configuration: 3-Pole, 4-Wire

Frequency (Hz): 60 Hz (60-Cycles)

Insulators Per Pole: 3

Protection Method:

Protection Type:

Protection Fuses:

Protection Ampacity: 4000A

Mains Rating (Amps): 4000A

Interrupting Rating: 200 kA @ 34.5 KV AC

Disconnect Means: Manual via Handle

Operating Mechanism: Adjustable open/close stops, Padlock-able in both open and closed positions, Equipped with: 1½" IPS vertical pipe, Minimum 1" IPS interphase pipe, Clamp-on open/close indicators (Green: Open; Red: Closed)

Motor Operation Provisions: N/A

Ratings

NRTL Listed Service Equipment

NRTL Listed to UL 891 Dead Front Switch Boards

NEMA 3R Rated for Indoor and Outdoor Use

Complies with ANSI C37.30

Complies with ANSI C37.32

Complies with ANSI C37.34

Complies with NEMA SG-6

Made in the USA

Features

Corona-free design

Arc horns included

High-strength insulators

RIV levels must match insulator ratings (open/closed positions)

Neutral Connection: Insulated Groundable Neutral Kit with Bonding Strap

Line-Out: N/A (customer provided)

Line-Out Cord Cap: N/A (customer provided)

Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0

Line-Out Orientation: Bottom Feed

Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door

Live Parts Material: Hard drawn or extruded (preferred); castings x-ray certified free of porosity/cracks

Bearings: Ball Type, (maintenance-free, permanently lubricated), Factory-adjusted, Water/dust ingress protected, Outboard bearings small contact area, wear-resistant

Terminal Pads: Ductile, high-conductivity material, machined top and bottom, NEMA 4-hole pattern

Contacts: Reverse loop design for magnetic short-circuit pressure boost, Silver-to-silver contact surface (≥ 1 mil) plating, Stainless steel coil spring-backed, insulated from current path, Wiping action on hinge/break-jaw; shunts not allowed, Rotary motion stop ensures consistent pressure regardless of operating speed

Mounting Height: Base height matched to 18 ft bus height

Door: (1) Left Hinged Door w/ Pad Lockable Handle

Enclosure Material: 11GA Sheet Steel

Enclosure Finish: ANSI 49 Grey

Enclosure Type: NEMA 3R Ventilated

Dimensions: 59.1"-L x 39.4"-W x 90.55"-H

Weight: 4500 lbs

Shipping Dimensions: -

Shipping Weight: -

Note: To close the contact, prime the switch first with the lever and then push the button. To open the contact, push the button. It requires a minimum of 600V AC.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-DS-FM-NFDS-3P-4W-34.5KV-4000A-DF-BM-N3R-GO-VB-M1 Power Distribution Air Disconnect Switch is designed for reliable, safe and convenient power distribution at industrial work sites. Designed for floor mounting installations, the bottom feed disconnect switch is protected by a NEMA 3R rated, steel enclosure with a ventilated design.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MPD-DS-FM-NFDS-3P-4W-34.5KV-4000A-DF-BM-N3R-GO-VB-M1 service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with three-phase 35 KV AC Delta or Wye, the disconnect switch features a manual operating handle. This bottom feed disconnect carries a 200 kA at 34.5 KV AC interrupt rating. The disconnect switch comes with and accepts three 4000-amp 35 KV ratings. An insulated groundable neutral kit with bond strap is included for neutral connections.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power.

Enclosure Design: The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI 49 grey finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor and outdoor areas.

Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the service entrance disconnect on floors and flat surfaces.

Customization: The MPD-DS-FM-NFDS-3P-4W-34.5KV-4000A-DF-BM-N3R-GO-VB-M1 can be customized to meet specific operating and power requirements. Example of customizations include:

- Making the disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single-pole camlock connectors for quick connections
- Adding heaters for cold environments
- Aiding alarm relays for trip notification downstream
- Adding power meters

Applications: This switch is suitable for indoor/outdoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs