

VFD-3P-240.208V-2HP-7.5A-DCM-N3R

2HP Variable Frequency Device - 240/208V AC 3PH Input/Output - 7.5 Amps (HD) - 1.5kW - NEMA 3R

Product ID: 326159



Image: VFD-3P-240.208V-2HP-7.5A-DCM-N3R

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

VFD-3P-240.208V-2HP-7.5A-DCM-N3R Variable Frequency Device

Unit Type: 3 Phase Delta, 3 Wire Variable Frequency Device

Dimensions: 4.33"-W x 5.47"-D x 5.12"-H

Weight: 3.75 lbs

Input Voltage: 240/208V AC 3PH, 50/60 Hz $\pm$ 5%

Output Voltage: 240/208V AC 3PH

Current Rating: 7.5 Amps (Heavy Duty), 8 Amps (Normal Duty)

Operating Frequency: 0 to 599 Hz

Kilowatts: 1.5

HP: 2

Braking: Requires a min. of 160 Ω external resistor (not supplied)

Starting Torque: 1 Hz/150%

Carrier Frequency: 2.0-15.0kHz, auto adjusted according to temperature and load

Frequency Accuracy: Digital setting: 0.01Hz, Analog Setting: Max frequency X 0.05%

Torque boost: Automatic torque boost; manual torque boost: 0.1%~30.0%

V/f curve: Linear, multiple point and square type (1.2 power, 1.4 power, 1.6 power, 1.8 power, square)

Inputs: 5 on-off programmable digital, 1 high-speed pulse, 2 programmable analog (AI1: 0~10V or 0/4~20mA AI2: 0~10V or 0/4~20mA)

Outputs: 1 programmable open collector, 1 analog (open collector or high-speed pulse), 1 Relay Contact Set, 2 Digital outputs

Analog Input/Output: 2 Input (0~10V or 0/4~20mA), 21 Output (0/4~20mA or 0~10V)

EMC Filter: N/A

Brake Chopper: Included, Built-In

Features/Ratings

Automatic Voltage Regulation

LED Display

3 Phase Delta, 3-Wire Configuration

Communication Terminal: RS485 communication interface, support MODBUS-RTU communication protocol

Overload: 150% @ 60s, 200% @ 0.5s

Operating Temp: -10°C to +50°C

Frame Size: B1

Enclosure Rating: NEMA 3R

Ventilation Space: 3.94 inches Above and Below, 0 inch Sides (@ 40°C ambient), 0.4 inch Sides (@ 50°C ambient)

Max Operating Humidity: 90% (non condensing)

Materials: -

Mounting: Wall Mount or Cubicle Mount via (4) 3/16" Diameter Holes at rear on 4.65" x 3.82" Centres

Color: Gray

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The VFD-3P-240.208V-2HP-7.5A-DCM-N3R from Larson Electronics is a 3 Phase, 3-Wire Configuration Variable Frequency Drive that is suitable for improving AC motor performance in industrial operations. This fan-cooled unit features a three-phase 240/208V AC input/output voltage compatibility. Designed for steady speed error, fast torque rise and protection from resonance vibrations, the device provides an output current of 7.5 amps (Heavy Duty) and an operating frequency range of 0 to 599 Hz with 2 horsepower.

The VFD-3P-240.208V-2HP-7.5A-DCM-N3R offers accurate AC motor control in industrial facilities. This 1.5 kW unit is compatible with three-phase nominal 240/208V AC input/output voltage, provides an output current of 7.5 amps and an operating frequency range of 0 to 599 Hz. This device supports seven on-off programmable digital inputs, one high-speed pulse input and two programmable analog inputs, as well as one programmable open collector output, one analog output (open collector or high-speed pulse), two relay outputs and two analog outputs. The device also features a total of four operating modes: Keypad control, Terminal control, Serial communication control, and Frequency Setting Mode for digital setting, analog setting, pulse frequency setting, serial communication setting, multi-step speed setting & simple PLC, PID setting, etc.

The VFD-3P-240.208V-2HP-7.5A-DCM-N3R is designed for indoor applications and operating temperatures ranging between -10°C to +50°C. Operators may mount the variable frequency drive on compatible surfaces. This device measures 4.33" x 5.47" x 5.12" and weighs approximately 3.75 lbs.

Applications: Speed control of AC motors, industrial machines, large compressors, energy savings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.











Frequently Asked Questions (FAQ)

There are no Faqs