

MT-K13-1P-208V-25KVA-120.240V-N4

25 kVA Transformer - 208V Primary - 120/240V Secondary - NEMA 4 - Single Phase - K-13

Product ID: 326818



Image: MT-K13-1P-208V-25KVA-120.240V-N4

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-K13-1P-208V-25KVA-120.240V-N4 K-13 Transformer

Phase: Single Phase
Frequency: 60 Hz
kVA: 25
Primary Voltage: 208V
Taps: 2 @ 2.5% FCAN; 4 @ 2.5% FCBN
Secondary Voltage: 120/240V
Winding Material: Aluminum
Electrostatic Shield: Yes
Insulation: 220°C
Temperature Rise: 150°C
K Factor: K-13
Terminations: Terminals
Enclosure Material: NEMA Type 4 Heavy Duty Ventilated
Finish: ANSI 61 Grey Finish
Dimensions: 24.39"-L x 19.37"-D 25.5"-H
Weight: 441 lb
Mounting: Floor Mount

Ratings

NRTL Listed for United States and Canada
Dry Type
IP66 Rated
K13 Rated

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-214-616-6180
E-mail: sales@larsonelectronics.com

The MT-K13-1P-208V-25KVA-120.240V-N4 from Larson Electronics is a 208V 1 Phase Energy Efficient K-13 Transformer that is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-K13-1P-208V-25KVA-120.240V-N4 provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions, and lower cost of

ownership make this transformer ideal for a wide range of applications and businesses.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

Transformer Features: With a transformer rating of 25 kVA and a K-factor of K-13, the MT-K13-1P-208V-25KVA-120.240V-N4 transformer is a single phase unit with a primary voltage of 208V. It also provides a secondary voltage of 120/240 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This transformers carries a K-Factor of K-13. The larger the K-Factor, the more harmonics that are produced in the load. This type of transformer uses a special winding technique that is designed to minimize eddy current losses that generated by harmonic currents in the load.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 4 enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP66.

Benefits: The MT-K13-1P-208V-25KVA-120.240V-N4 general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Applications: General purposes that require a K13 rated transformer including telecommunications equipment and branch circuits in classrooms and healthcare facilities.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



LARSON
ELECTRONICS™

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664





Frequently Asked Questions (FAQ)

There are no Faqs