Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-PLB-2MVA-208.480.600V-60HZ-N4X-M2

2 MVA Portable Load Bank (Resistive) - 208 x 480 x 600V Rated, 3-Phase, 4-Wire, 60 Hz, Caster Wheels, NEMA 4X, Yellow and Black, W/ Air Duct, W/ Cables

Product ID: 326924



Image: MPD-PLB-2MVA-208.480.600V-60HZ-N4X-M2

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-PLB-2MVA-208.480.600V-60HZ-N4X-M2 Portable Load Bank

Unit Type: Portable Load Bank, Resistive
Load Element: Alloy Resistors
Load Voltage: 208 x 480 x 600V AC, 3Ph, 4 Wire
Nominal Frequency: 50/60 Hz
Rated Power: 2 MVA (2000 KW Resistive Load), Continuous Duty, At 600V, Compensated at 208V
Load Steps: 3 phase synchronous: 10, 20, 30, 40, 50*2, 100*4, 200*3, 400KW*2
Insulation Class: F
Power Factor: 1.0
Load Accuracy: ±5%

Load Resolution: 10 KW

Display: Real time display of voltage, current, power, frequency and other parameters

Wire Connection: L1, L2, L3 and N

Cooling Mode: Forced air cooling, air entry from side and outlet to the top

Air Flow: 28,500 CFM, Vertical Direction

Temperature Rise: 48.89°C

Max. Air Intake Temperature: 93.33°C

Power Supply: 3 phase AC480V, 60Hz

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 1008
NRTL Listed to UL 98
Outdoor Type

CSA, UL Certified

Made in the USA

Features

Compact load bank unit with user friendly control panel.
Effectively applied for full load test of generator set, UPS and other AC power systems.
Sectionalized control of input power enables any customized setting of load step and time
Real-time display of test current, voltage, power, power factor, time and frequency.
Alternative control modes by local control of circuit breaker/push button or PC control
Emergency stop button for quick termination of AC load test
Protection upon over load, over voltage, over temperature, short circuit and so on
It adopts latest load element with high density power, safer and more durable
Axial flow fans with big blast capacity for quick ventilation

with low noise

Power Input Connections: Camlocks

Way of Control: Local + PC remote control

Resistive Load Elements: Composed of multiple special alloy resistors in parallel. The outer part of the alloy resistor is made of 304 stainless steel sheet as the heat-dissipating material, the outer tube is made of 304 stainless steel tube as anti-rust and anti-corrosion component. The inside is filled with the Magnesium Oxide powder which is thermal conductive and insulating medium, and the power consumption component Nickel-Chromium alloy resistor is packaged therein

Protection: Emergency stop button, over temperature alarm and over temperature/over voltage protection

Standard Parts: AC power cord and RS485-USB cable

Standard of Essential Parts: Contactor: UL, PLC: CE (Siemens)

Data Logging: Included

Air Duct: Included

Cables: Included, 100ft, 6*300MCM for each phase.

Handling: With forklift position, with casters at bottom

Wheels: Included

Operating Atmospheric Pressure: 86 - 106kPa

Operating Temperature: -10°C to +50°C

Humidity: 5-90%

Altitude: 8,202 ft Above Sea Level

Noise Level: 75 dbA

Protection Level: IP56 when storage, IP20 during operation. This is outdoor type and can be placed outdoors. However, it cannot be tested on rainy days. If test on rainy days is required, air duct installation is needed.

Enclosure Finish: Yellow and black

Enclosure Type: NEMA 4X, 316L Stainless Steel

Mount: On Caster Wheels

Dimensions: 78.7"-W × 157.5"-D × 86.6"-H

Weight: 2645.6 lbs

Shipping Dimensions: TBD

Shipping Weight: TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-PLB-2MVA-208.480.600V-60HZ-N4X-M2 Portable Load Bank is essential for maintenance to ensure your generator performs to the required engine wattage. Normally a generator runs at a level less than its rated output; therefore a load bank test provides an artificial load to ensure the generator is running at the correct wattage if needed.

The MPD-PLB-2MVA-208.480.600V-60HZ-N4X-M2 portable load bank provides a safe and reliable way for operators in industrial settings to test generators' wattage. Compatible with three-phase 208 x 480 x 600V AC, the PLB features 2000 KW minimum load step resolution. This 3-phase load bank carries a 2000 KVA at 208 x 480 x 600V AC operating voltage.

Operation: The MPD-PLB-2MVA-208.480.600V-60HZ-N4X-M2 features a locking door. The door provides access to a permanently attached operating handle.

Enclosure Design: This portable load bank is a compartmental design. The housing is fabricated from 316L stainless steel. The front electrical enclosure carries a NEMA 4X rating. Two hinged exterior doors allow for access into the compartments. A steel plate allows for underground conduit entry into the enclosure compartments. A removable steel plate at the base of the power compartment prevents rodents and other intrusions from entering the enclosure once installed. Four removable caster wheels are installed in the load bank base to enable easy movement.

Certification: This PLB is NRTL listed to UL 98 and UL 1008, as well as NRTL listed for service equipment.

Mount: Mounted on wheels

Applications: This Load bank has a wide variety of applications such as: Generator servicing, generating set exercising and / or testing, keeping generating set above minimum loading (load shedding), battery discharge and UPS systems exercising, and /or testing to reduce 'Wet Stacking' problems and ground power testing.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs