Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R

2.5 KVA Uninterruptible Power Supply - 120/208/240/480V 1PH 60 Hz Input - 120/208/480V 1PH 60 Hz Output - NEMA 3R

Product ID: 327483



Image: MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R Uninterruptible Power Supply

Unit Type: Uninterruptible Power Supply

Dimensions: 17.05" x 7.48" x 12.52"

Weight: 88 lbs

Input Voltage: 120/208/240/480V AC 1PH, 60Hz

Output Voltage: 120/208/480V AC 1PH, 60Hz

Output Power Capacity: 2 KW/2.5 KVA

Max Configurable Power: 2 KW/2.5 KVA

Output Voltage Distortion: Less Than 3%

Crest Factor: 3:1, Double Conversion Online

Waveform Type: Sine Wave

Battery Type: Supports both battery and kinetic energy storage options

Recharge Time: Typically around 2 hours, depending on the battery type and load conditions

Filtering: Full-time Multi-pole Noise Filtering: 0.3% IEEE Surge Let-through: Zero Clamping Response Time

Interface: DB-9 RS-232 , RJ-45 10/100 Base-T, Smart-Slot

Pre-Installed SmartSlotT Cards: AP9619

Control Panel: LED Status Display with Load and Battery Bar-graphs; On Line, On Battery,

Ratings/Approvals

Replace Battery, Overload and Bypass Indicators
Audible Alarm: Alarm When on Battery, Distinctive Low Battery Alarm and Overload Continuous Tone Alarm

Emergency Power Off (EPO): Yes

Operating Temp: 0°C to 40°C

Operating/Storage Relative Humidity: 0-95%

Operating Elevation: 0-10,000`

Storage Temp: -15°C to 45°C

Storage Elevation: 0-50,000`

Materials: -

Hardware Material: Zinc Plated Steel
Enclosure Finish: Aluminum Lacquer Paint
Mount: Surface Mount
Input Connections: Hardwire 4-wire (3PH + N)
Output Connections: (1) Hardwire 4-wire (3PH + N) (Battery Backup) ,
Bypass: Internal
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Special Orders - Special Requirements
Contact us for special requirements
Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R is an advanced Industrial Uninterruptible Power Supply (UPS) suitable for demanding environments like data centers, healthcare facilities, and large industrial plants. This UPS unit operates on a single-phase 120/208/240/480V AC supply and features an adaptable design that accommodates both battery and kinetic energy storage systems.

The MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R provides comprehensive battery backup support for essential equipment in industrial and commercial settings. This 2.5 kVA UPS system features a single-phase 120/208/240/480V AC 60Hz input and 120/208/480V AC 60Hz output. The unit is equipped with an output power capacity of 2 kW / 2.5 kVA and supports dynamic ride-through capabilities, allowing it to handle voltage dips of up to -50% without immediate reliance on stored energy.

Key Features: Energy Storage Options: The unit supports both traditional battery storage and kinetic energy storage systems. The battery option uses a maintenance-free sealed lead-acid battery with a suspended electrolyte, designed to be leakproof and reliable. The recharge time for the battery is approximately 2 hours, depending on the load and battery type.

Dynamic Voltage Compensation: This UPS system can manage significant voltage dips without switching to stored energy or generator support, making it highly resilient in fluctuating power conditions.

High Efficiency: The MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R operates with an efficiency of up to 98% in online mode, minimizing energy losses and operational costs.

Control and Monitoring: The UPS features a sophisticated control panel with LED status displays and monitoring graphs, enabling real-time monitoring and configuration. The system supports self-diagnostics and predictive maintenance to ensure continuous operation and reduce the need for frequent shutdowns.

Interfaces: Available interface ports include DB-9 RS-232, RJ-45 10/100 Base-T, and a

Smart-Slot for additional communication options. These interfaces facilitate easy integration with network management systems and remote monitoring solutions.

Input and Output Wiring: The unit accepts hardwire, 2-wire (1PH + N) input connections. It provides similar output connections: (1) Hardwire, 2-wire (1PH + N) (Battery Backup), allowing seamless integration into existing electrical infrastructure.

Noise Filtering and Alarms: The sine-wave UPS includes full-time multi-pole noise filtering and an audible alarm system to signal real-time operational status, low battery, and overload conditions.

Operating Conditions: The unit is designed for optimal performance in varying environmental conditions with an operating temperature range from 0°C to 40°C and can operate at altitudes up to 10,000 feet. It is housed in a weatherproof outdoor enclosure, making it suitable for both indoor and harsh outdoor environments.

Mounting: The MT-UPS-1P-120.208.240.480V-2.5KVA-120.208.480V-R1-N3R Series UPS is compatible with surface mounting applications, providing flexibility in installation across different facilities

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664




Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs