

RFUSE-CC-600V-3A-TD

Class-CC Time-Delay Fuse – 600V AC – 3A Rated

Product ID: 327671



Image: RFUSE-CC-600V-3A-TD

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

Class CC Time-Delay Fuse – 600V AC – 3A Rated

Current rating: 3A

Voltage Rating AC: 600V

Fuse Class: Class-CC (UL 248-4)

Blow Characteristic: Time-Delay (Slow-Blow) – Suitable for motor/fan inrush

Interrupting Rating: 200 kA @ 600V AC

Body Style: Ceramic Cartridge Fuse

Construction: Melamine/Ceramic Tube with Nickel-Plated End Caps

Mounting Style: Fuse Holder (Class-CC Fuse Block)

Termination Style: Clip

Operating Temperature: –40°C to +85°C

Indicator: w/o

Dimensions: 10.3 mm × 38.1 mm (13/32" × 1.5")



Frequently Asked Questions (FAQ)

There are no Faqs