

**MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1**

**5 MVA Pad Mount Transformer - 34500V Delta Primary, 13200V Delta Secondary - ONAN/Bell Green**

**Product ID: 327889**



Image: MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1 3PH Pad Mount Transformer**

**Transformer Type:** Pad Mounted, Compartmental-Type  
**Transformer Configuration:** Liquid Filled Pad Mounted  
**Transformer Feed Type:** Loop Feed  
**Operation:** Step-Down Operation (Not Approved for Step-Up)  
**Phase:** Three Phase  
**Capacity:** 5 MVA (5000 KVA)  
**Vector Group:** Dyn1  
**Primary Voltage:** 34500V  
**Primary Voltage Switch:** N/A  
**Primary Voltage Class:** 35 kV Class  
**Primary Phasor:** Delta  
**Primary BIL:** 150 KV  
**Secondary Voltage:** 13200V  
**Secondary Voltage Class:** 15 kV Class  
**Secondary Phasor:** Delta  
**Secondary BIL:** 95 KV  
**Frequency:** 60 Hz  
**Temperature Rise:** 55/65°C  
**Insulation Rating:** Class E Insulation - 120°C, 248°F  
**Cooling Class:** ONAN; Self-Cooled  
**Forced Air (Fans):** None  
**Tap Changer:** 5-position De-Energized Tap Changer  
**Tap Qty:** (2) FCAN Above Taps, (2) FCBN Below Taps  
**Tap %:** 2.5%

**Ratings**

Meets/Exceeds DOE 2016 Efficiency Ratings  
Meets/Exceeds CSA Efficiency Ratings  
Complies with ANSI / IEEE C57.12.00  
Complies with ANSI / IEEE C57 12.28  
Complies with ANSI / IEEE C57 12.29  
Complies with ANSI / IEEE C57 12.34  
Complies with ANSI / IEEE C57 12.35  
Complies with ANSI / IEEE C57.12.70  
Complies with ANSI / IEEE C57.12.110  
Complies with ANSI / IEEE C57.12.131  
Complies with ANSI / IEEE C62.11  
Complies with ANSI / IEEE C62.22  
Complies with ANSI / IEEE 386  
Complies with ANSI / IEEE C2  
Complies with ANSI / IEEE C37.47  
Complies with ANSI Z535.4  
Complies with ASTM D3487  
Complies with ASTM D6871  
Complies with NEMA 260-1996  
Complies with 10 CFR Part 431  
Complies with CSA C2.1-06  
Complies with CSA C50  
Complies with CSA C88  
Complies with CSA C88.1

**Tap Changer Switch Rating:** 300-Amp, 35 kV  
**Tap Changer Switch Location:** High Voltage (HV) [Left Side] Front Compartment  
**Impedance:** 5.0-7.5% Typical  
**Primary Connection Type:** Dead Front  
**Primary Termination Arrangement:** V Terminal Arrangement  
**Primary Termination:** Externally Clamped Integral Bushings w/ Removable Studs, 600A Dead Break Elbows  
**Primary Connection Qty:** (6) Primary Connections for use w/ Elbow Connectors  
**Primary Parking Stand Qty:** (6) Welded Brackets for Installing Accessory Parking Stand Bushings  
**Primary Bushing Rating:** 35 kV Class, 200 kV BIL, 600A, Dead Break, IEEE 386 Color Brown  
**Primary Neutral Connection:** N/A  
**Primary Surge Arrestors:** Included, (3) High Voltage Elbow Surge Arrestors  
**Primary Surge Arrestor Voltage Rating:** 36 kV Class Elbow Arrestor  
**Primary Surge Arrestor MCOV Rating:** 29 kVrms  
**Primary Overcurrent Protection (OCP):** Bayonet Expulsion Fuses w/ Backup Current-Limiting Fuses  
**Primary Overcurrent Protection Method:** Fused, Oil-Immersed  
**Primary Overcurrent Protection Holder:** Bayonet Fuse Holder w/ Flapper Valve and External Drip Shield  
**Primary Grounding Provisions:** (1) NEMA Ground Bar attached to tank via (2) Welded Ground Bungs in HV Cabinet  
**Secondary Connection Type:** Live Front  
**Secondary Termination Arrangement:** Inline Terminal Arrangement  
**Secondary Connections:** NEMA Spade Terminals, 14-Hole Spade, Externally Clamped, Accepts up to (14) Double Lug connections with (7) cables per side of Spade connector  
**Secondary Connection Qty:** (3) Externally Clamped One-Piece Epoxy Bushings Copper Threaded Studs  
**Secondary Connection Supports:** N/A  
**Secondary Overcurrent Protection (OCP):** N/A  
**Secondary Neutral Connection:** N/A  
**Secondary Grounding Provisions:** (1) NEMA Ground Bar attached to tank via (2) Welded Ground Bungs in LV Cabinet  
**Metering Current Transformer (CT):** N/A  
**Metering Panel:** N/A  
**Auxiliary Control Panel:** N/A  
**Load Break Switch:** 4-Position Load Break Switch  
**Load Break Switch Qty:** (1)  
**Load Break Switch Rating:** 300-Amp, 35 kV  
**Load Break Switch Location:** High Voltage (HV) Front Compartment  
**Efficiency Standard(s):** Meets DOE 2016 Standards, Meets CSA Standards Meets ANSI/IEEE Standards  
**K-Factor Rating (Harmonic Mitigation):** K-1 (Standard)  
**Pulse Drive Rating:** N/A  
**Insulation Fluid:** Mineral Oil Insulating Fluid, Non-PCB Fluid  
**Fluid (Oil) Capacity\*:** 700 Gallons  
**Fluid (Oil) Weight\*:** 5,390 Lbs  
**Liquid Level Indicator:** Analog Dial Gauge  
**Temperature Indicator:** Analog Dial Gauge  
**Pressure/Vacuum Indicator:** Analog Dial Gauge  
**Pressure Relief Device:** Included, Automatic Action  
**Fault Indicator:** N/A  
**Gas Sampler Valve:** Included, Schrader Valve  
**Fill Valve:** 1" NPT Port w/ Removable Bolt Plug  
**Fill Valve Location:** Front Compartment  
**Drain Valve:** 1" NPT Port w/ 5/8" NPT Sampler Valve  
**Drain Valve Location:** Front Compartment  
**Winding Material:** Copper  
**Ambient Temperature Rating:** 40°C  
**Ambient Operating Temperature Range:** -40°C to +40°C (-50°F to +104°F)  
**Sound Level:** 65 dBA

Complies with CSA C88-16  
Complies with CSA C227.4  
Complies with CSA C227.5  
Complies with CSA C802-3  
Complies with CSA C802.1

#### **Features**

Penta-head Bolt Entry Assembly  
  
High-Fire Point Insulating Fluid  
Non-PCB Insulating Fluid  
Tamper Proof Housing  
Hinged Front Compartment Doors, Pad Lockable  
NEMA 3R Wiring Compartment  
  
Hot Stick Included, HV Door Mount

**Efficiency %:** 98.00%

*Based on transformer operating at 50% of nameplate base kVA.*

#### **Load Losses Based on 85°C Reference Temp.**

**No Load Loss (in watts):** +/- 8,889W

**Full Load Loss (in watts) at 100%:** +/- 34,996W

**Total Load Loss (in watts) at 100%:** +/- 43,885W

#### **Total Losses at 55°C LL Temp. & 20°C NL Temp.**

**Total Load Loss (in watts) at 50%:** +/- 17,640W

**Note:** Losses offered are typical only, not guaranteed

#### **Labeling:**

Externally Stencilled (Painted) KVA Rating  
Externally Stencilled (Painted) Voltage Rating  
External Non-PCB Label  
External Warning & Danger Label  
  
External Barcode Label  
  
Internal Busing & Accessory Labeling  
Stainless Steel Riveted Nameplate

#### **Factory Tests:**

Winding Resistance Test  
Insulation Resistance Test  
Voltage Ratio Error Test  
Short-circuit Impedance Test  
No-load Loss (Wattage) Test  
Load Loss (Wattage) Test  
Induced Voltage Withstand Test  
Separate Source Voltage Withstand Test  
Pressure Integrity Test

#### **Shipping:**

Shipped on pallet on open flatbed  
Palletized on Wooden Pallet w/ Skid Pockets  
Pallet Skid Facing Outward Sides of Truck

**Note:** Crated shipping in lieu of palletizing can be done upon request for an additional fee

**Elevation (Altitude):** 3300ft (1000 meters) Above Sea Level  
**Core Material:** Grain Oriented Steel  
**Tank Material:** Coated Steel  
**Cabinet Material:** Coated Steel  
**Base Platform Material:** Coated Steel  
**Portability:** Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding  
**Housing Type:** Compartmental Air-Filled Cabinet w/ Locking Doors, HV Compartment Left, LV Compartment Right, Steel Barrier Separation, HV Door Spring-Loaded Release Pin in LV Compartment  
**Enclosure Rating:** NEMA 3R Weatherproof Wiring Cabinet, Sealed Tank  
**Seismic Rating:** Yes  
**Paint Type:** Weatherproof and UV Resistant Epoxy Coating and Undercoating  
**Finish Color:** Munsell™ 7.0 GY 3.29/1.5 Bell Green  
**Mounting:** Pad Mounted  
**Conduit Opening:** Bottom Feed Underground Entry/Exit  
**HV Compartment Base Wireway Dimensions\*:** 21"-W x 7"-D  
**LV Compartment Base Wireway Dimensions\*:** 26"-W x 9"-D  
**MV/LV Compartment Cabinet Depth\*:** 24"-D  
**Tank Cover Access Handhole:** N/A  
**Dimensions\*:** 96"-W x 108"-D x 94"-H  
**Dry Weight (w/o Oil)\*:** 10,462 Lbs  
**Total Weight (Liquid Filled)\*:** 16,518 Lbs

\*Please note that numbers are approximate and subject to change

#### **Special Orders - Special Requirements**

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-903-270-1187

**Fax:** 1-903-765-7664

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**The MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1 from Larson Electronics is an Industrial Pad Mount Transformer that offers powerful, reliable, and efficient power distribution in indoor, outdoor, and public locations. The low operating costs, low heat emissions, and low cost of ownership make this transformer ideal for a wide range of applications and businesses. An enclosed design caters to installations on concrete pads without protective fencing.**

***\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\****

**Transformer Features:** With a transformer rating of 5000 KVA (5 MVA), the pad-mount transformer features a primary voltage of 34,500V Delta and a secondary voltage of 13,200V Delta for MV-to-MV step-down operation. The unit is equipped with a loop-feed design for utility-style installation and dead-front separable connectors. A 5-position de-energized tap changer provides (2) +2.5% and (2) -2.5% taps to compensate for utility voltage variation.

Copper transformer winding material helps improve performance, reduce weight and lower cost. Compared to aluminum, copper windings have lower eddy losses due to higher resistivity. This transformer consists of a rectangular coil and a five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1 is air cooled and does not have fans or mounting provisions for fans.

**Enclosure Design:** This pad mounted transformer is a compartmental design. The tank and housing are fabricated from steel. The front electrical enclosure carries a NEMA 3R rating. The high voltage and low voltage compartments are located in front of the transformer tank, with the high voltage compartment on the left side and low voltage compartment on the right side.

The HV and LV compartments are air filled and separated by a full length steel barrier between the compartments. A removable steel plate at the base of the HV and LV compartments prevents rodents and other intrusions from entering the enclosure once installed. This steel plate allows for underground conduit entry into the enclosure compartments. Two hinged exterior doors allow for access into the compartments. A single pad lockable handle on the low voltage compartment door allows for securing the transformer. A spring loaded pin within the low voltage compartment prevents the high voltage door from being opened without pulling the safety pin. A hot stick is included in the high voltage compartment, mounted to the HV door.

**Temperature Rise:** This unit features 55/65°C temperature rise for high-efficiency operation and extended service life. The combination of low temperature rise and high efficiency make this unit suitable for outdoor pad mounting in utility and renewable energy applications.

**Insulation Fluid:** The MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1 features mineral oil cooling fluid (ONAN) with a capacity of 700 gallons. We offer transformers with biodegradable or FR-3 oil fluids, if needed.

**Biodegradable Fluid:** Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% load conditions, which helps preserve the transformer's lifespan and performance.

**Gauges:** The following gauges are included with the system: liquid level, temperature and pressure/vacuum gauges. Standard liquid level, temperature and pressure/vacuum gauges are analog, manual reading types. These gauges do not have auxiliary contacts.

**Fault Pressure Devices:** This transformer features an automatic action fault pressure device. Fault pressure devices are used to detect high rates of pressure rise within the tank.

**Rapid Rise Relay:** There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.

**Surge arresters:** This system comes with high elbow surge arresters on the primary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without high elbow surge arresters that have mounting provisions for customer-provided surge arresters.

**Valves:** The MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1 is equipped with a pressure relief valve, fill valve, and drain valve with sampler port.

**Protection Fuses:** This transformer contains bayonet expulsion fuses with backup overcurrent protection inside the oil compartment.

**Mount:** The heavy-duty enclosure makes the unit suitable for both indoor and outdoor

applications. This power distribution system can be pad mounted on concrete pads.

**Benefits:** The MT-PML-R7-3P-DMA-5MVA-DMQ-LT-DF-A6-CM-CZ-2H4-M1 pad mount transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

**Applications:** Utility interconnection, BESS auxiliary service, commercial power distribution, MV backup power, substations, industrial facilities, renewable energy, electrical infrastructure expansion, and general medium-voltage distribution.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) to discuss your specific requirements.



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664



Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.765.7664





---

## Frequently Asked Questions (FAQ)

There are no Faqs