

EXPCMR-IP-POE-8MP-IR-V2-LWS

Explosion Proof Network IP Camera - 8.0MP Resolution - 15FPS - Low Light IR Array - Liquid Washer System

Product ID: 330668



Image: EXPCMR-IP-POE-8MP-IR-V2-LWS

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXPCMR-IP-POE-8MP-IR-V2-LWS Network Explosion Proof Camera

Unit Type: Explosion Proof Security Camera

Dimensions: -

Weight: -

Total Watts: 5W (Max)

Power Source: PoE (802.3af)

Image Sensor: 1/2.7" Progressive Scan CMOS sensor

Signal System: NTSC

Video Resolution: 8MP (3840*2160)

Frame Rate: 15fps (3840*2160)

Compression Type: H.265, H.264, MJPEG

Bit Rate: 128Kbps - 16Mbps

Focal Length: 2.8mm @F1.6, Fixed-focal

Max Field of View: 83°

Shutter Speed: Auto/Manual, 1 ~ 1/1000000s

Min. Illumination: 0.01 lux (Color), F1.6, AGC ON

IR Range: 45 ft

Day/Night: True D/N w/Mechanical Cut Filter

Digital Noise Reduction: 2D/3D DNR

Ethernet Interface: RJ45

Ethernet Speed: 10/100

Protocols: IPV4, IPV6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL, TLS, SSH

Remote Configuration: Yes

Ambient Temperature Range: -22°F to +140°F

Quick Summary

Class I, Divisions 1 & 2 Groups B,C,D

Class I, Zones 1 & 2 Groups IIB+H2, IIA

Class II, Divisions 1 & 2 Groups E,F,G

Class III, Divisions 1 & 2

Ex db IIC Gb

Ex tb IIC Gb Db IP66

NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)

Liquid Washer System w/ Female Connector

Main Stream w/ (2) Sub-streams

Program Unique Settings per Stream

ONVIF (Profile S, Profile G, Profile T), API, SDK

120dB True Wide Dynamic Range for Auto-adjusting

NDAA Compliant

Special Orders - Special Requirements

Contact us for special requirements

Housing Materials: Copper-free Aluminum Alloy
Lens Material: 3/8" Tempered Glass
Mounting: Adjustable Rear-mounted Handle/bracket
Wiring Hub: (2) 3/4" NPT

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The EXPCMR-IP-POE-8MP-IR-V2-LWS Network Explosion Proof Camera from Larson Electronics is a remote inspection camera specifically designed for observation in hazardous locations. This explosion proof, dust/ignition proof, weather proof and tamper resistant camera provides the operator with a live feed from inside tanks, reactors, vessels or other hazardous locations. Operated remotely from a centralized control room, this remote inspection camera saves both time and money as well as contributing to workplace safety. The unit features a liquid washer system with a female stainless steel connector, located at front of the camera lens for proactive clarity.

Camera Features: The EXPCMR-IP-POE-8MP-IR-V2-LWS Network Explosion Proof Camera features a built-in 1/2.7" progressive-scan CMOS image sensor that delivers up to 8.0MP resolution at 15 fps. The wide angle fixed lens with 83° field of view covers a large area, and an integrated IR LED array provides the operator with low light and nighttime visibility up to 45'. The camera automatically switches from full color to IR mode when visible light falls below a certain level. This remote inspection camera utilizes Advanced Infrared Technology, 120dB true Wide Dynamic Range, 3D Digital Noise Reduction and a true day/night IR-Cut filter Removal to produce clear images in variable and low light conditions. This explosion proof camera provides a crisp and clear image for everything within the 83° focal area. Total distance is dependent on mounting height and angle.

Wiring: Link-up with the camera is achieved via a customer provided RJ45 Ethernet cable which is ran back to the customer provided DVR system mounted outside the hazardous location. Camera power is delivered via the same Ethernet cable using Power over Ethernet (PoE) technology. This not only increases flexibility in deployment, but also provides time and cost savings as well.

Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 – 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 – 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

Recording: To record the stream from this camera, an NVR (network video recorder) is required. Larson Electronics provides a line of explosion proof, hazardous location, and non-classified NVR's to work in conjunction with this explosion proof camera. This camera is live-view capable without an NVR system via remote access to the camera. Three streams are available, one main stream for recording and two sub streams for live viewing or additional resources. Each stream can be configured to different resolutions and frame rates.


Mounting: The EXPCMR-IP-POE-8MP-IR-V2-LWS Network features an ATEX/IECEX

certified copper-free aluminum alloy body and weighs a total of 6 pounds. The camera includes an adjustable rear-mounted polished stainless steel mounting bracket/handle. Additional accessory pole mounts and magnetic mounts are available separately.

Applications: Vessel, tank and reactor monitoring, remote observation of external facilities, monitoring of cleaning, spray patterns, mixing, foaming, reaction, and level.


At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

	8	7	6	5	4	3	2	1
REV	DESCRIPTION							DATE
A	PRODUCTION RELEASE							8/3/2026
EXPCMR-IP-POE-8MP-IR-V2-LWS 								
	8	7	6	5	4	3	2	1



TAGS	QTY	CATALOG	DESCRIPTION
1-101.15	1	UNV00015838	8MP IP Bullet 98 IR 2.8mm WDR Ultra H.265

 LARSON ELECTRONICS 9419 E US HWY 175, KEMP, TX 75143	TITLE EXPCMR-IP-POE-8MP-IR-V2-LWS		
	DRAWN BY M.ASHRAF	DATE 08-03-2026	REV A
	CHECKED BY J.MALDONADO	SHEET # 1 OF 1	DRAWING # 101











Frequently Asked Questions (FAQ)

There are no Faqs