Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-MT-UPS-3P-208Y.120V-25KVA-208Y.120V-R1-N1

25 KVA Uninterruptible Power Supply (UPS) Inverter System – 208Y/120V 60Hz 3PH Input, 208Y/120V 60Hz 3PH Output – 20 KW – 125 VDC Station Battery

Product ID: 330937



Image: MPD-MT-UPS-3P-208Y.120V-25KVA-208Y.120V-R1-N1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MT-UPS-3P-208V-25KVA-208V-R1-N1 Inverter System (UPS Functionality)

Unit Type: Inverter System – Online Double Conversion, Parallel Modular, N+1 Redundant

Dimensions: *Floor-Mounted Cabinets; dimensions vary by inverter, bypass, and battery configuration*

Weight: *Varies by cabinet configuration*

Input Voltage: 208V AC, Line-to-Line, Three Phase, 4-Wire + Ground, +10% / −15% (without affecting output)

Input Frequency: 60 Hz ±5%

Load Power Factor Range: 1.0 to 0.8 lagging

Input THD: ≤5%

Output Voltage: 208V AC, 3-Phase, 3-Wire + Ground

Output Frequency: 60 Hz

Regulation: ±1% steady state

Voltage THD: ≤5% (linear load), ≤7% (50% non-linear load)

Load power factor range: Unity power factor with the ability to support 0.8 leading to 0.8 lagging without derating

Efficiency in double conversion mode: ≥89% at full rated kW

Parallel capability: Up to four distributed; contact factory for more information

Output Power Capacity: 25 kVA / 20 kW

Max Configurable Power: 25 kVA / 20 kW

Ratings/Approvals

Inverter Modules: (2) × 15 kVA / 12.5 kW inverter modules, (1) additional inverter module for N+1 redundancy

Module Type: Hot-swappable, front-accessible

Crest Factor: 3:1, Double Conversion Online

Waveform Type: Sine Wave

Nominal DC Voltage: 125 VDC

DC Voltage Window: +20% / −25%

Battery Type: Station Battery System

Battery Protective Device: Provided per inverter module, lockable in OFF position

Charging Method: External charger per station battery system

Recharge Time: Per station battery system design

Backup Time: 15 minutes @ 20 kW full load

kAIC: ≥10 kA symmetrical (minimum), system-coordinated

Filtering: Full-time multi-pole noise filtering; IEEE C62.41 compliant surge protection

Interface: RS-232, Ethernet (RJ-45), Modbus / SNMP capability

Pre-Installed SmartSlotT Cards: AP9619

Control Panel: Front-mounted control/indicator panel with digital metering

Audible Alarm: Audible and visual alarms for inverter, battery, bypass, and system faults

Emergency Power Off (EPO): Yes

Operating Temp: 0°C to 40°C (32°F to 104°F)

Operating/Storage Relative Humidity: 0-95% non-condensing

Operating Elevation: 0-10,000`

Storage Temp: −20°C to +60°C (−4°F to +140°F)

Storage Elevation: 0–40,000 ft

Materials: Heavy-duty steel cabinets

Hardware Material: Zinc Plated Steel
Enclosure Finish: Aluminum Lacquer Paint
Mount: Floor-Mounted Cabinets
Input Connections: Hardwire, 4-Wire (3PH + N + GND)
Output Connections: Hardwire, 4-Wire (3PH + N + GND) (Battery Backup)
Bypass: Integral Static Bypass Transfer Switch and External Maintenance Bypass – Make-Before-Break (Closed Transition)
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Special Orders - Special Requirements
Contact us for special requirements
Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The MPD-MT-UPS-3P-208Y.120V-25KVA-208Y.120V-R1-N1 is an Industrial Inverter System with UPS functionality designed for critical loads in work sites, substations, and large facilities. This battery-backed inverter system operates on three-phase 208Y/120V AC input and three-phase 208Y/120V AC output and provides uninterrupted power through an online double-conversion design. An integrated control panel with digital display enables real-time monitoring, status indication, and system control.

The MPD-MT-UPS-3P-208Y.120V-25KVA-208Y.120V-R1-N1 provides reliable battery backup support for customer-provided equipment in critical power applications. This 25 kVA / 20 kW parallel modular inverter system features three-phase 208Y/120V AC, 60 Hz (±5%) input and three-phase 208Y/120V AC, 60 Hz output. The system is configured with multiple hot-swappable inverter modules arranged in an N+1 redundant architecture, ensuring continuous operation during maintenance or module failure. Power is supplied from a 125 VDC station battery system, providing 15 minutes of backup runtime at full 20 kW load.

This sine-wave inverter system includes an integral static bypass transfer switch and an external make-before-break (closed-transition) maintenance bypass, allowing the inverter system to be isolated without interrupting the critical load. The system features full-time multi-pole noise filtering, coordinated fault protection, and comprehensive audible and visual alarms for inverter, battery, overload, and bypass conditions. The front-mounted control panel provides detailed system metering, including input/output voltage, current, frequency, kW, kVAR, kWh, battery voltage, and battery current.

Wiring: This system accepts hardwire 4-wire (3PH + N + GND) input connections. Output connections are provided via hardwire 4-wire (3PH + N + GND) terminals for battery-backed critical loads.

Mounting: The MPD-MT-UPS-3P-208Y.120V-25KVA-208Y.120V-R1-N1 is supplied in floor-mounted, heavy-duty steel cabinets with front access for maintenance and service.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs