

MT-PML-XX-SP9658

200A Loadbreak Cable Adapter – 15 kV Class – Compatible with 5 kV Systems

Product ID: 331617

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PML-XX-SP9658 T Loadbreak Cable Adapter

Features

Unit Type: Loadbreak Cable Adapter (Bushing Interface)

Rated Voltage □ Phase-to-Phase: 15 kV Class (Compatible with 5 kV Systems)

Withstand Voltage (50/60Hz): 34 kV / 1 min

BIL and Full Wave Crest: 95 kV

Load break Ratings (at 80% pf): 200 A

Cable Diameter Range: 0.64" to 1.05"

Stranded or Compressed Conductor Size: 4 AWG Compact Copper

Dimensions: Approx. 6.5" L x 4.5" W x 5.5" H

Weight: Approx. 3.5 lbs

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Replacement Primary Bushing Cable Adapter – 15 kV Class, 200 A (Compatible with 5 kV Systems)

200 A Loadbreak Bushing Interface, 15 kV Class, 95 kV BIL, IEEE 386 T-
Body Loadbreak Connector for 4 AWG Compact Copper Cable

Frequently Asked Questions (FAQ)

There are no Faqs