Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1

15 kV Electrical Metering Cabinet, Combinations (CT/PT) - 3-Phase - Dry Type - Pole Mount, Outdoor Service

Product ID: 332717



Image: MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1 Electrical Metering Cabinet Combinations (CT/PT)

Unit Type: Electrical Metering Cabinet (EMC)
Unit Configuration: Combinations Current & Voltage Transformer (CT/PT), Dry Type
Rated Frequency: 60 Hz

Phase: Three Phase

Wiring Configuration: 4-Wire

CT Specifications:

Quantity: (3)

Rated Voltage: 15 kV
Current Ratio: 200:5
CT Design Form: Wound

Accuracy Class: 0.15S Class

Secondary Terminals:

- Provided with a manual shorting device
- Suitable for terminating #14 through #4 AWG copper conductors
- Sealable protective cover provided

Ratings

Complies with ANSI / IEEE C57.13
Complies with ANSI / IEEE C57.13.6
Meets/Exceeds IEEE C57.12.28
Meets IEEE 386 for 200A separable load-break connectors

Warranty

Failure of any component due to defective design, material, or workmanship within 12 months of energization or 18 months from delivery, whichever occurs first, shall be repaired or replaced at no cost.

PT Specifications:

Quantity: (3)

Primary Voltage: 12470V Delta

Primary Voltage Class: 15 KV

Secondary Voltage: 72V

Voltage Ratio: 100:1

Accuracy Class: 0.15 Class

Thermal Burden: 1500 VA @ 30°C

Primary Protection: Primary fuse mounted on each PT

BIL: 110 kV BIL

Main Bus Rating: 200A continuous

Bus Bracing: 20 kA symmetrical / 28 kA asymmetrical

Bus Material: Copper

Jumpers: Fused jumpers from main bus to CTs and VTs, Insulated for 15 kV

Dead-Front Terminations: 200A Separable Load-Break Bushings

Dead-Front Bushings Per Phase: One (1) 200A Load-Break Bushing Well

Radial Feed: One (1) 200A load-break connection per phase

Test Switch Type: 10-pole, reversed potentials, ST terminals, Lexan cover

Test Switch Location: Right interior wall of CT/PT compartment

CT Wiring: #10 AWG solid copper

VT Wiring: #12 AWG solid copper

Color Coding: VA Orange, VB Blue, VC Yellow, VN White, CT-A Black, CT-B Brown, CT-C Red, CTR Gray

Terminal Order: VA, VB, VC, VN, CTR-A, CT-A, CTR-B, CT-B, CTR-C, CT-C

Meter Socket: External mounting provision per EUSERC 339

Continuous Thermal Current Rating Limit Factor (rf): 1.5

Dead-Front Bushings Per Phase: (1) 200A Load-Break Bushing Well

Meter Socket: External mounting provision per EUSERC 339

Grounding Bosses: Four (4) total, 1/2-13NC tapped holes, 7/16" deep, two per compartment; accepts #6 solid to #2/0 stranded copper.

Compartment Layout: Separate CT/PT and cable termination compartments, located on opposite sides of enclosure.

Phase To Ground Compartment Barriers: Red Reinforced Polyester

Fault Venting: Tamper-proof stainless screened vents rated for 10kA, 15 cycles.

Winding Material: Copper

Service Condition: Outdoor

Roof: Domed or sloped to prevent standing water

Base: Sealed bottom to prevent access to animals and foliage, Screened drain vents provided for drainage in case of flooding

Altitude: N/A

Ambient Temperature Rating: N/A

Door Safety: Internal door safety barrier

Hardware Materials: Stainless Steel

Terminator Parking Stands: Welded stainless steel, quantity suitable for number of bushings provided

Enclosure Class: NEMA 4X, Outdoor

Nameplate Materials: Corrosion Resistant Stainless Steel w/ Stainless Steel Screws or Rivets For CT & VT

Markings: Manufacturer Name, Manufacturer Serial Number, Nominal Operating Voltage, Rated Current, BIL, Equipment Manufacture Date, One-line diagram showing CT and PT ratios
Paint Color: Munsell™ 7GY 3.29/1.5 Bell Green
Mounting Provisions: Pole Mount
Lifting Provisions: Included
Spare Parts: three (3) spare primary fuses for the PTs.
Dimensions: 31.5" x 78.7" x 31.5"
Weight: 661.4 lbs

Special Orders- Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1 Electrical Metering Cabinet from Larson Electronics is designed for power utility applications in outdoor locations. The low operating costs, low heat emissions and low cost of ownership make this transformer an ideal solution for metering, high voltage system control and more. This cabinet is compatible with pole mounting installations.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Cabinet Features: The MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1 is rated for 15 kV, 60 Hz. The system has heavy-duty windings for high strength and thermal/electrical conductivity.

Insulation Fluid: The MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1 is a dry type.

Primary Connections: The cabinet has NEMA 4-inch, 2-hole copper pad terminals for primary connections. The terminal conducting surface is horizontal. The current transfer point is tinned or silver plated.

Secondary Connections: This CT/PT has accessible terminal blocks for secondary connections. The terminal block is protected by a weatherproof, metal junction box located on the transformer base housing and features a large access door. Operators can access three 1.5" openings for completing connections.

Mount: The MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1 is pole mounted.

Benefits: The MPD-EMC-R7-3P-DMR-15KV-YV-200.5CT-N4X-M1 cabinet offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Applications: Electric power distribution, utilities, utility power generation, power grids, substations, metering, high voltage system control and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs