Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1

75/100/125-137.5 MVA Substation Power Transformer, Conservator Type - 138000Y/79674 Grounded Wye Primary, 69000Y/39387 Grounded Wye Secondary, 13800V Delta Tertiary - ONAN/ONAF/ONAF, 55-65°C, Mineral Oil, Sky Grey, NEMA 4X

Product ID: 333734



Image: MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1 Conservator Transformer

Transformer Type: Substation Power Transformer, Conservator Type
Transformer Configuration: Liquid Filled
Transformer Feed Type: N/A
Operation: Step-Up Operation (Not Approved for Step-Down)
Phase: Three Phase
Capacity (w/o Fans, @ 55°C): 75 MVA (75,000 KVA)
Capacity (w/ 1st Stage Fans, @ 55°C): 100 MVA (100,000 KVA)
Capacity (w/ 2nd Stage Fans, @ 55°C): 125 MVA (125,000 KVA)
Capacity (w/ 2nd Stage Fans, @ 65°C): 137.5 MVA (137,500 KVA)
Vector Group: YNyn0d1
Primary Voltage: 138000Y/79674
Primary Voltage Switch: N/A
Primary Voltage Class: 145 KV
Primary Phasor: Grounded Wye
Primary BIL: 650 KV
Primary Neutral BIL: 200 KV
Secondary Voltage: 69000Y/39387
Secondary Voltage Class: 72.5 kV Class
Secondary Phasor: Grounded Wye
Secondary Line BIL: 350 KV
Secondary Neutral BIL: 200 KV
Tertiary Voltage: 13800V (Buried)
Tertiary Phasor: Delta

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.29
Complies with ANSI / IEEE C57 12.34
Complies with ANSI / IEEE C62.22
Complies with ANSI / IEEE C62.11
Complies with ANSI / IEEE 386
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.110
Complies with ANSI / IEEE C57.12.131
Complies with CSA C802.1
Complies with CSA C88
Complies with CSA C88.1
Complies with CSA C88-16
Complies with ANSI / IEEE C2
Complies with ANSI / IEEE C37.47
Complies with ANSI Z535.4
Complies with CSA C227.5
Complies with CSA C227.4
Complies with CSA C50

Frequency: 60 Hz
Temperature Rise: 55/65°C
Insulation Rating: Class A Insulation
Cooling Class: ONAN/ONAF/ONAF
Forced Air (Fans): Included, Two Stages

Tap Changer: 33-Position ON-Load Tap Changer
Tap Qty: (16) FCAN Above Taps, (16) FCBN Below Taps
Tap %: 5/8%
Tap Changer Switch Rating: 145 KV
Impedance (@ 75 MVA): 16%
Primary Connection Type: Live Front
Primary Termination Arrangement: Inline, Top Mounted
Primary Termination: w/ NEMA 4-Hole Pad connectors
Primary Bushing Qty: (4)
Primary Bushing Rating: 145 KV Class, 650 KV BIL, Porcelain
Primary Neutral Connection: Included
Primary Surge Arrestors: N/A
Primary Surge Arrestor Voltage Rating: N/A
Primary Surge Arrestor MCOV Rating: N/A
Primary Overcurrent Protection (OCP): N/A
Primary Line Bushing CT: Included, (2) Per Each Phase (600:5 MR, 10L400 Accuracy Class), (2) Per Each Phase (600:5 MR, 0.3 B-0.23 Accuracy Class)
Primary Neutral Bushing CT: Included, (1) 800:5 MR, 10L400 Accuracy Class
Primary Overcurrent Protection Holder: N/A
Primary Grounding Provisions: Included
Secondary Connection Type: Live Front
Secondary Termination Arrangement: Inline, Top Mounted
Secondary Termination: NEMA 4-Hole Pad connectors
Secondary Bushing Qty: (4)
Secondary Bushing Rating: 72.5 KV Class, 350 KV BIL, Porcelain
Secondary Neutral Connection: Included
Secondary Overcurrent Protection (OCP): N/A
Secondary Line Bushing CT: Included, (3) Per Each Phase (1200:5 MR, 10L400 Accuracy Class)
Secondary Neutral Bushing CT: Included, (1) 800:5 MR, 10L400 Accuracy Class
Secondary Surge Arrestors: N/A
Secondary Surge Arrestor Voltage Rating: N/A
Secondary Surge Arrestor MCOV Rating: N/A
Secondary Grounding Provisions: Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Connection To 2/0 to 500 KCMIL Stranded Copper conductor
Neutral Bushing CT: N/A
Metering Current Transformer (CT): Included
Metering Panel: Included
Auxiliary Control Panel: Included, Contains Power Sources 125 Vdc, 120/240 Vac-1Ph
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Rating: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Mineral Oil, Non-PCB Fluid
Fluid (Oil) Capacity*: TBD
Fluid (Oil) Weight*: 59524.81
Silica Gel Breather: Included, Type dehydrating electrical for main transformer and tap changer
Liquid Level Indicator: Included, (1) for main conservator and (1) for tap changer conservator
Winding Temperature Indicator: Included, Type (MR) use for control fan and protect from extra heating for high voltage side and it has two contacts for trip and alarm

Complies with ASTM D3487
Complies with ASTM D6871
Complies with NEMA 260-1996
Complies with 10 CFR Part 431
Complies with CSA C2.1-06
Complies with CSA C802-3
Complies With IEEE Std 693-2018

Features
Penta-head Bolt Entry Assembly
High-Fire Point Insulating Fluid
Non-PCB Insulating Fluid
Tamper Proof Housing
NEMA 4X Wiring Compartment
Hinged Front Compartment Doors, Pad Lockable
Hot Stick Included, HV Door Mount

Efficiency %: N/A
Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 75°C Reference Temp.
Off-Load Loss (in watts): 21800W, ±10% Tolerance
On-Load Loss (in watts): 120890W, ±10% Tolerance
Total Load Loss (in watts) at 100%: TBD

Total Losses at 55°C LL Temp. & 20°C NL Temp.

Total Load Loss (in watts) at 50%: TBD
***Note:** Losses offered are typical only, not guaranteed*

Labeling:
Externally Stenciled (Painted) KVA Rating
Externally Stenciled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

Factory Tests:
Winding Resistance Test
Pressure Integrity Test
Insulation Resistance Test
Voltage Ratio Error Test

Liquid Temperature Indicator: Included, Type (MR) used for control fans and protect from extra heating and it has two contacts for trip and alarm
Pressure/Vacuum Indicator: Included, With Scale Range Of Plus Or Minus 10 PSI
Rapid Rise Relay: Included, (63) Qualitrol 910-013-03
Pressure Relief Device: Included, (1) for main tank and (1) for tap changer tank
On-Line DGA Device: Included, with the transmission data to control panel detection (H2, CO, CO2, CH4 , C2H4, C2H6 , C3 H8, O2 , N2) suitable for environment 550 C
Trolley Iron Base: Included
Pressure Reducer: N/A
Gas Relay: Included
Fault Indicator: Included, Buchholz Relay. 3" diameter
Gas Sampler Valve: N/A
Fill Valve: Included
Fill Valve Location: Top Mounted
Drain Valve: Included, 1.6" Globe Type With 3/8" Sampling Valve
Drain Valve Location:
Winding Material: Copper
Ambient Temperature Rating: 40°C
Ambient Operating Temperature Range: -20°C to +40°C
Sound Level: N/A
Elevation (Altitude): 3300ft (1000 meters) Above Sea Level
Core Material: Silicon Steel, Grain Oriented
Tank Material: Coated Steel
Cabinet Material: Coated Steel
Base Platform Material: Coated Steel
Hardware Material: Stainless Steel
Portability: Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
Housing Type: Metal Casing Liquid Filled Transformer
Enclosure Rating: NEMA 4X Weatherproof
Seismic Rating: Zone 1
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: ANSI #70 Sky Grey
Mounting: Supporting Structures
Conduit Opening: N/A
Tank Cover Access Handhole: Included
Dimensions: 235.43"-W, 157.48"-D, 240.16"-H
Dry Weight (w/o Oil)*: 146,000 Lbs
Total Weight (Liquid Filled)*: 196,000 Lbs
*Please note that numbers are approximate and subject to change

Separate Source Voltage Withstand Test
Short-circuit Impedance Test
Induced Voltage Withstand Test
No-load Loss (Wattage) Test
Load Loss (Wattage) Test

Shipping:
Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
Note: *Crated shipping in lieu of palletizing can be done upon request for an additional fee*

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1 Conservator Substation Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in outdoor locations. The low operating costs, low heat emissions, and low cost of ownership make this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The conservator transformer should be installed on supporting structures.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The industrial transformer features a primary voltage of three-phase 138000Y/79674 Grounded Wye and a secondary voltage of three-phase 69000Y/39387 Grounded Wye. This system is rated for 75 MVA (natural cooled), 100 MVA (1st stage fan cooled), and 125 MVA (2nd stage fan cooled). We offer systems with loop or radial feed, as well as dead front or live front primary connections. The transformer features a 33-position

ON-load tap changer with sixteen +5/8% taps above and sixteen -5/8% taps below to allow small changes in voltage. There is a rapid rise relay present on the system.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of a rectangular coil and a five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1 has fans for forced air cooling and pumps for forced oil cooling. This non-sealed system features breathers for cooling when operating temperatures increase.

Temperature Rise: This unit features 55/65°C temperature rise for reduced heat waste, increased reliability and longer life. At 55°C temperature rise, the transformer offers 75 MVA (natural cooled), 100 MVA (1st stage fan cooled), and 125 MVA (2nd stage fan cooled). At 65°C temperature rise, the transformer offers 137.5 MVA (2nd stage fan cooled). The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in outdoor areas.

Insulation Fluid: The MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1 features mineral oil insulation fluid (ONAN/OFAF). We offer transformers with biodegradable or FR-3 fluids, if needed.

Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% load conditions, which helps preserve the transformer's lifespan and performance.

Gauges: The following gauges are included with the system: liquid level indicator, fluid temperature indicator, winding temperature indicator, and pressure/vacuum indicator. Standard liquid level, temperature and pressure/vacuum gauges are analog dial types.

Fault Pressure Devices: There is a rapid pressure rise relay and seal-in relay on this unit.

Gas Relay: A gas relay with indicators for light gas and heavy gas is included with the transformer. The relay includes two Dry Type Form C auxiliary contacts (1NO + 1NC) for remote alarm when pressure rises above in-field set pressure located in auxiliary control cabinet.

Surge arresters: This system doesn't contain surge arresters.

Load Break Switch: The transformer is not equipped with a load break switch.

Valves: The MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1 is equipped with a pressure relief valve.

Protection Fuses: This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.

Mount: This conservator substation transformer is installed on supporting structures, such as the roof of the transformer main tank.

Benefits: The MT-PSTC-R7-3P-GXK-75MVA-GXA-HT-LT-X6-CMFF-CZ-1ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs