

MT-PML-XX-SP9677

LV Transformer Bushing – 2.5kV, 6500A, 6-H, 45kV BIL

Product ID: 334858

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PML-XX-SP9656 Apparatus Bushing

Unit Type: Porcelain LV Apparatus Bushing

Rated Voltage □ **Phase-to-Phase):** 2.5 kV

Maximum System Voltage: 2.5 kV Class

Withstand Voltage (50/60Hz): 10 kV / 1 min.

BIL and Full Wave Crest: 45 kV

Load break Ratings (at 80% pf): 6500A

Mounting Configuration: 6-Hole (6-H)

Insulation Type: Glazed Porcelain

Connection Type: Stud / Spade Terminal

Conductor Material: Tin-Plated Copper

Operating Temperature: -40°C to +130°C

Dimensions: 17"-L x 8"-D

Weight: 55lbs

Features

IEEE C57.19.00 / IEC 60137

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

LV Transformer Bushing – 2.5kV, 6500A, 6-H, 45kV BIL



Frequently Asked Questions (FAQ)

There are no Faqs