Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPCS-4XPL-1XSLSW-HL-M1

Explosion Proof Control Station - C1D1/C2D1 - (4) PL, (1) Selector Switch - Hinged Lid, (5) 3/4" NPT Hubs, (1) 1 1/2" NPT Hubs

Product ID: 335097

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPCS-4XPL-1XSLSW-HL-M1 Explosion Proof Control Station

Listing: United States - Canada
Internal Dimensions: 24" (610mm) L x 12" (305mm) H x 8" (203mm) D
External Dimensions: 16.38" (416.05mm) L x 28.38" (720.85mm) H x 11.32" (287.53mm) D
Pan Dimensions: 10.25" (260.4mm)L x 22.25" (565.2mm)W
Available Dimensions for Devices: 11.37" (288.8mm) L x 23.37" (593.6mm) H x 8.00" (203.20mm) D
Weight: -
Maximum Conduit Size: 2" NPT
Voltage (Lights): 24V AC/DC
Maximum Operators on Lid: 9 (3 rows of 3)
Row 1 Lights: (4) Green, Short Barrel
Row 2 Equipment: (1) 20A 2P Double Throw, Rotary On/Off Selector Switch
Row 3 Equipment: -
Total Hub Quantity: 6
Lid (Top) Hubs: 0
North Side Hubs: (1) 1 1/2" NPT Hub
South Side Hubs: (3) 3/4" NPT
East Side Hubs: 0
West Side Hubs: (2) 3/4" NPT Hub
Bottom (Back/Base) Hubs: 0
Conduit: Operator Provided
Operating Window: N/A
Lid Type: Hinged Lid
Hinges Material: N/A
Internal Mounting Pan Included: Yes
Internal Mounting Pan Taps: (6) 3/8" NPT [four corners]
Internal Mounting Pan Material: Aluminum
Internal Mounting Pan Dimensions: 10.25" (260.4mm)L x 22.25" (565.2mm)W
Internal Grounding Lug: N/A
Breather Plug: N/A
Drain Plug: N/A
Ambient Operating Temp Range:-30° C to +85°C
Operating Temp Rating: T5/T6 Rated
Enclosure Material: Copper Free Cast Aluminum (less than 4/10 of 1%)

Features/Ratings

Listed for United States & Canada
Class I, Divisions 1 & 2, Groups C, D
Class I, Zones 1 & 2, Groups IIB, IIA
Class II, Divisions 1 & 2, Groups E, F, G
Class III, Divisions 1 & 2
NEMA 3R, 4, 7 (C, D), 9 (E, F, G)
NRTL Listed to UL 508A
NRTL Listed to UL 1203
NRTL Listed to CSA C22.2 No 14, 25, 30
See Drawing for Hub Placements

Hardware Material: Zinc Plated Steel

Enclosure Finish: Aluminum Lacquer Paint; custom available

Mounting: Surface Mount Legs

Mounting Leg Height: 0.19"

Mounting Dimensions (Horizontal) Height: N/A
Mounting Dimensions (Horizontal) Width: N/A
Mounting Dimensions (Vertical) Height: 6" Center to Center
Mounting Dimensions (Vertical) Width: 9.88" Center to Center
Shipping Weight: 85 lbs
Shipping Dimensions: TBD
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The Larson Electronics EPCS-4XPL-1XSLSW-HL-M1 Explosion Proof Control Station provides operators with a Class I and II, Division 1 and 2 cast aluminum enclosure designed to hold electrical equipment up to 24" by 12" by 8" in size. Operators may access four green pilot lights and one rotary selector switch on the device. This explosion proof station is ideal for indoor or outdoor applications where flammable vapors, gases, or dusts exist or stand the potential to exist.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES

The EPCS-4XPL-1XSLSW-HL-M1 is made of cast aluminum, equipped with steel bolts and includes a weatherproof gasket for a NEMA 3R / NEMA 4 protection rating. This hazardous location device is NEMA 7 (Groups B, C, and D) and NEMA 9 (Groups E, F, and G) rated. The internal cavity of this flameproof enclosure measures 24" in length by 12" in width by 8" in height. five 3/4" NPT hubs and one 1 1/2" NPT Hub. Equipped with a hinged lid, a removable aluminum backplate for secure mounting of operator equipment is included.

This explosion proof unit features the following operators: Row 1- (4) green pilot lights; Row 2- (1) 20A double throw on/off rotary selector switch. The lights on the explosion proof control station are offered in 24V AC/DC.

Click Photos to Enlarge



Click To Enlarge



Click To Enlarge

Larson Electronics can customize each unit with drilled and tapped operator hubs and/or conduit hubs per customer request. Please view the above and below images for orientation. When looking at the top cover (labeled Lid), all four sides are labeled for the orientation when looking at the Lid. All hubs are CNC machined for precision. Please see below specifications table for included taps and dimensional drawing for exact locations.



Click To Enlarge



Click To Enlarge

Construction: Each unit in the EPL-AED series is certified to NEC standards for United States and CEC Canada. We offer an ATEX/IEC Ex model for global applications (ATEX-EPL-AED series). These explosion proof enclosures are NEMA 3R rated, for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4X equipment can be equipped upon request. NEMA 4X models include all stainless steel external hardware. Operator lid hinges can be fitted on the enclosure for regular opening and closing. Breather plugs, drain plugs, and grounding lugs can be added at customer request.

Customization: Larson Electronics can customize this explosion proof enclosure for compatibility with existing systems, assemblies, work flows and processes or assist in designing units for new installation. We can add indicator lights, windows, hinges, operator handles, push button switches, momentary push button switches, emergency stop push buttons, selector switches, on/off switches, terminal blocks, relays, PLCs, mounting pans and more. Customized labels are also available for each operator in order to meet various requirements.

Unless otherwise specified in the specification tables and drawing, each unit comes without factory conduit hub taps. Conduit openings can be tapped on all sides and back of the explosion proof enclosure. Tapping of conduit hubs is facilitated at Larson Electronics using a CNC machine for precise cutting. Larson Electronics offers customization on conduit opening size and locations. Taps include female NPT (National Pipe Thread), female BSPT (British Standard Pipe Thread), and Metric ISO thread. Please contact us for specific requirements. Additional equipment can be provided from factory, including nipples, unions, seal-offs, and operator devices.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Suggested Applications: The EPL-AED series of explosion proof enclosures are approved for use within indoor and outdoor environments where flammable or combustible gases, vapors, dusts, fibers, and flying exist or stand the potential to exist, and is ideal for a wide variety of applications.

Applications include but not limited to aircraft maintenance, alcohol processing, aerospace,

chemical manufacturing, coke processing, cold storage, compressed natural gas (CNG) facilities, cranes, cryogenics, distilleries, food processing, fuel storage, gas processing plants, grain processing, laboratories, liquefied natural gas (LNG) facilities, liquid propane gas (LPG), machine operations, manufacturing, marine vessels, methane production, mining, offshore, oil drilling rigs, oil refineries, paint spray booths, paper processing, petrochemical, petroleum refineries, pharmaceuticals, power plants, production refineries, sand blast cabinets, sewage and septic tanks, shipyards, solvent and cleaning areas, storage facilities, tank farms, tankers, textile, washdown areas, waste treatment plants, and woodworking. Click here to read the NEC description for explosion proof and hazardous locations.

REV	DESCRIPTION	DATE
A	PRODUCTION RELEASE	04-17-2026

EPCS-4XPL-1XSLSW-HL-M1-24VDC

LARSON ELECTRONICS®



TAGS	QTY	CATALOG	DESCRIPTION
LT1-101.05 LT1-101.05A LT1-101.05B LT1-101.05C	4	UNV00017861	PilotLight, Green with Lamp Holder & Lamp 24V AC/DC - Normal Length 25mm, 3/4 NPSM
SS1-101.12	1	UNV00019599	2 Position 2 Pole Double Throw Selector Switch - Normal Length 25mm, 3/4 NPSM

LARSON ELECTRONICS
9419 E US HWY 175,
KEMP, TX 75143

TITLE			
EPCS-4XPL-1XSLSW-HL-M1-24VDC			
DRAWN BY	DATE	REV	
J.Maldonado	04-17-2026	A	
CHECKED BY	SHEET #	DRAWING #	
	1 OF 1	101	

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs