

MV-ABC-15KV-336.4KCMIL

15kV Medium Voltage Aerial Bundled Cable, 336.4 kcmil Aluminum, Triplex, TR-XLPE Insulated, Steel Messenger - Sold by the Foot/2500' per Reel

Product ID: 335458



Image: MV-ABC-15KV-336.4KCMIL

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MV-ABC-15KV-336.4KCMIL Aerial Bundled Cable (ABC)

Unit Type: Medium Voltage Aerial Bundled Cable (ABC)

Voltage Rating: 15 kV Class

Configuration: 3C Triplex (Twisted) + Steel Messenger

Conductor: Aluminum (AAC / AAAC / ACSR – per spec)

Insulation Type: TR-XLPE (Tree-Retardant Cross-Linked Polyethylene)

Shielding: Non-Shielded (*typical for overhead ABC*)

Messenger: Galvanized Steel Messenger (Integral Support)

Insulation Level: 100% or 133%

Temperature Rating: 90°C Normal Operation

Application: Overhead Distribution, Utility Pole Lines, Tree Wire / Spacer Cable Systems

Dimensions: Power Station to Substation Connections

Weight: TBD

Features/Ratings

ICEA S-94-649 / AEIC CS8 / ASTM

Sold by the Foot (12")

One Reel Contains 2,500' of Cable

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The Larson Electronics MV-ABC-15KV-336.4KCMIL is a 15kV Medium Voltage Aerial

Bundled Cable, Triplex Aluminum Conductor, TR-XLPE Insulated, Non-Shielded, with Integrated Steel Messenger, rated for overhead utility distribution applications. This cable is designed for reliable performance in tree wire and spacer cable systems, with a 100% or 133% insulation level and a 90°C operating temperature.

This unit is sold by the foot (12"). One reel contains 2,500 feet of cable.



Frequently Asked Questions (FAQ)

There are no Faqs