Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU

3 kVA Isolation Transformer - 480V Delta Primary - 480Y/277 x 208Y/120 x 240Y/139 Wye-N Secondary - Fully Potted - NEMA 4X - Copper

Product ID: 336339



Image: MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU Fully Potted Isolation Transformer

Transformer Type: Isolation
Phase: Three Phase
Frequency: 60 Hz
Vector Group: Dyn1
Capacity: 3 kVA
Primary Voltage: 480 V Delta
Taps: -
Secondary Voltage: 480Y/277 x 208Y/120 x 240Y/139 V Wye-N
Hipot Test Voltage Level: 3 kV
Winding Material: Copper
Insulation: 180°C
Temperature Rise: 125°C
Impedance (Std): -
Efficiency: DOE 2016 / NRCAN 2019 (Also Meets ON Reg. 404/12)
Seismic: Yes
Ambient Temperature Range: -40°C to 60°C
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: Wire Leads
Secondary Termination: Wire Leads
Enclosure Material: NEMA Type 4X Heavy Duty
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: 11.13"H x 12.38"W x 5.44"D

Ratings

Listed for United States and Canada
ANN Cooling
NEMA 4X Rated
Isolation Transformer
Fully Potted
UL Listed

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

Weight: 70 lbs
Mounting: Wall Mount

Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU 3 kVA 3 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 3 kVA, the MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU isolation transformer is a three phase unit with a primary voltage of 480 V Delta. It also provides a secondary voltage of 480Y/277 x 208Y/120 x 240Y/139 V Wye-N. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The standard NEMA Type 4X enclosure makes the unit suitable for outdoor applications and it can be wall mounted. The unit also features 180°C insulation with a 125°C temperature rise.

Benefits: The MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material helps to improve performance. The close tolerances used during manufacturing also eliminate burrs, which hinder performance. Each core is specially coated to prevent the ingress of moisture and is electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Safety: The MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU is an isolation transformer, which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-FP-3P-480D-3KVA-480.208.240Y-N4X-CU achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power

distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs