Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-PLB-265KVA-480V-60HZ-N3R-M3

265 KVA Portable Load Bank - 480V Rated, 3-Phase, 60 Hz, Caster Wheels, NEMA 3R, Grey

Product ID: 336353



Image: MPD-PLB-265KVA-480V-60HZ-N3R-M3

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-PLB-265KVA-480V-60HZ-N3R-M3 Portable Load Bank

Unit Type: Portable Load Bank
Line-In: N/A
Line-In Connections: Terminal Lugs
Line-In Orientation: Bottom Feed
Capacity (@ 480V): 265 KW
Capacity (@ 240V): 257 KW
Capacity (@ 415V): 198 KW
Capacity (@ 208V): 192 KW
Rated Voltage: 480V AC
Load Step Resolution: 5 kW at 480V (Can be done while energized)
Overall Load Tolerance: -0, +5%.
Power Factor: 1.0
External Control Capability: Included
Control Power Requirement: External 120V, 1-Phase, 60Hz, 15A
Cooling System: Integral TEFC or TEAO motor with direct coupled cooling fan
Frequency: 60 Hz
Resistor Elements: Helically wound chromium alloy Helidyne elements
Communication Ports: USB, RS232
Wheels: Included, (2) moveable and (2) fixed casters
Operating Temperature: -28°C to +50°C
Construction Material: Heavy gauge aluminized steel (ASTM A463)
Fasteners Material: Stainless steel
Enclosure Finish: Baked polyester powder coat (ANSI 61 gray)

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 1008
NRTL Listed to UL 98
NEMA 3R Rated for Indoor/Outdoor Use
Two Years Warranty
Made in the USA

Safety Features

Exhaust temperature sensors
Electrically interlocked load steps
Short circuit protection fuses
15A control/blower circuit fuse

Enclosure Type: NEMA 3R Ventilated
Mount: Portable/Floor Mount
Dimensions: 26.45"-W, 51.92"-D, 46.86"-H
Weight: 600 lbs
Shipping Dimensions: TBD
Shipping Weight: TBD
Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-PLB-265KVA-480V-60HZ-N3R-M3 Portable Load Bank is essential for maintenance to ensure your generator performs to required engine wattage. Normally a generator runs at a level less than its rated output; therefore a load bank test provides an artificial load to ensure the generator is running at the correct wattage if needed.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-PLB-265KVA-480V-60HZ-N3R-M3 portable load bank provides a safe and reliable way for operators in industrial settings to test generators' wattage. Compatible with three-phase 480V AC, the PLB features 5 KW load step resolution. This 3-phase load bank carries a 265 kVA (265 KW) at 480V AC operating voltage.

Operation: The MPD-PLB-265KVA-480V-60HZ-N3R-M3 features a locking door. The door provides access to a permanently attached operating handle.

Enclosure Design: This portable load bank is a compartmental design. The housing is fabricated from steel. The front electrical enclosure carries a NEMA 3R rating. Two hinged exterior doors allows for access into the compartments. A steel plate allows for underground conduit entry into the enclosure compartments. A removable steel plate at the base of the power compartment prevents rodents and other intrusions from entering the enclosure once installed. Four removable caster wheels are installed in Load bank base to enable easy move.

Certification: This PLB is NRTL listed to UL 98 and UL 1008, as well as NRTL listed for service equipment.

Mount: portable or floor mount.

Applications: This Load bank has a wide variety of applications such as: Generator servicing, generating set exercising and / or testing, keeping generating set above minimum loading (load shedding), battery discharge and UPS systems exercising, and /or testing to reduce ‘Wet Stacking’ problems and ground power testing.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at

800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs