Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3

15 kV Electrical Metering Cabinet, Combination CT/PT, 3-Phase, Dry Type – ACUVIM II Power & Energy Meter – Pad Mount, Outdoor Service

Product ID: 336459



Image: MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3 Electrical Metering Cabinet Combinations (CT/PT)

Unit Type: Electrical Metering Cabinet (EMC)
Unit Configuration: Combinations Current & Voltage Transformer (CT/PT), Dry Type
Rated Frequency: 60 Hz

Phase: Three Phase, 3 Wire

Metering Device: ACUVIM II Series Advanced Power & Energy Meter | ANSI C12.20 Class 0.2 Accuracy
Meter Functions: Voltage, Current, Power, Energy, Frequency, Power Factor, Harmonics Monitoring

CT Specifications:

Quantity: (3)

Rated Voltage: 15 kV
Current Ratio: 200:5
CT Design Form: Wound
Accuracy Class: 0.15S Class

Secondary Terminals:

- Provided with a manual shorting device

Ratings

Complies with ANSI / IEEE C57.13
Complies with ANSI / IEEE C57.13.6
Meets/Exceeds IEEE C57.12.28
Meets IEEE 386 for 200A separable load-break connectors

Warranty

Failure of any component due to defective design, material, or workmanship within 12 months of energization or 18 months from delivery, whichever occurs first, shall be repaired or replaced at no cost.

- Suitable for terminating #14 through #4 AWG copper conductors
- Sealable protective cover provided

PT Specifications:

Quantity: (3)

Primary Voltage: 7,200V (for 12,470Y/7,200V system)

Primary Voltage Class: 15 KV

Secondary Voltage: 120V

Voltage Ratio: 7200:120
Accuracy Class: 0.15 Class

Thermal Burden: 1500 VA @ 30°C

Primary Protection: Primary fuse mounted on each PT

BIL: 110 kV BIL

Main Bus Rating: 600A continuous

Bus Bracing: 20 kA symmetrical / 28 kA asymmetrical

Bus Material: Copper

Jumpers: Fused jumpers from main bus to CTs and VTs, Insulated for 15 kV

Dead-Front Terminations: 200A Separable Load-Break Bushings

Dead-Front Bushings Per Phase: One (1) 200A Load-Break Bushing Well

Radial Feed: One (1) 200A load-break connection per phase

Test Switch Type: 10-pole, reversed potentials, ST terminals, Lexan cover

Test Switch Location: Right interior wall of CT/PT compartment

CT Wiring: #10 AWG solid copper

VT Wiring: #12 AWG solid copper

Color Coding: VA Orange, VB Blue, VC Yellow, VN White, CT-A Black, CT-B Brown, CT-C Red, CTR Gray

Terminal Order: VA, VB, VC, VN, CTR-A, CT-A, CTR-B, CT-B, CTR-C, CT-C

Meter Socket: External mounting provision per EUSERC 339

Continuous Thermal Current Rating Limit Factor (rf): 1.5

Dead-Front Bushings Per Phase: (1) 200A Load-Break Bushing Well

Minimum clearances measured from live part to bare metal:
- Phase-to-Ground: 6.0 inches minimum
- Phase-to-Phase: 7.5 inches minimum
Additional stationary barriers provided to allow reduced clearance of 3.0 inches from barrier to live parts.

Meter Socket: External mounting provision per EUSERC 339

Metering Device: ACUVIM II Series Advanced Power & Energy Meter

Meter Display: Backlit LCD multifunction display

Meter Communication Ports: RS-485 / Ethernet

Metering Parameters: kW, kVAR, kVA, PF, Voltage, Current, Frequency, kWh, THD

Grounding Bosses: Four (4) total, 1/2-13NC tapped holes, 7/16" deep, two per compartment; accepts #6 solid to #2/0 stranded copper.
Compartment Layout: Separate CT/PT and cable termination compartments, located on opposite sides of enclosure.

Phase To Ground Compartment Barriers: Red Reinforced Polyester

Fault Venting: Tamper-proof stainless screened vents rated for 10kA, 15 cycles.

Winding Material: Copper

Service Condition: Outdoor

Roof: Domed or sloped to prevent standing water

Base: Sealed bottom to prevent access to animals and foliage, Screened drain vents provided for drainage in case of flooding

Altitude: N/A

Ambient Temperature Rating: N/A

Door Safety: Internal door safety barrier

Hardware Materials: Stainless Steel

Terminator Parking Stands: Welded stainless steel, quantity suitable for number of bushings provided

Enclosure Class: NEMA 3R Weatherproof, Aluminum

Nameplate Materials: Corrosion Resistant Stainless Steel w/ Stainless Steel Screws or Rivets For CT & VT

Markings: Manufacturer Name, Manufacturer Serial Number, Nominal Operating Voltage, Rated Current, BIL, Equipment Manufacture Date, One-line diagram showing CT and PT ratios

Paint Color: Munsell™ 7GY 3.29/1.5 Bell Green
Mounting Provisions: Pad Mount
Lifting Provisions: Included
Spare Parts: three (3) spare primary fuses for the PTs.
Dimensions: 59.06"-W x 49.21"-D x 59.06"-H
Weight: 661.4 lbs

Special Orders- Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3 Electrical Metering Cabinet from Larson Electronics is designed for utility-grade power monitoring and metering applications in outdoor and industrial locations. This heavy-duty EMC integrates combination current transformers (CTs), voltage transformers (PTs), and an ACUVIM II Series advanced power and energy meter for accurate electrical system monitoring, energy measurement, and power quality analysis. The cabinet is compatible with medium voltage power distribution systems and pad mounting installations.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Cabinet Features: The MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3 is rated for 15 kV, 60 Hz, three-phase operation. The system features dry-type CT/PT construction with copper buswork and dead-front separable load-break terminations. The integrated ACUVIM II Series Power & Energy Meter provides multifunction monitoring of voltage, current, power, energy consumption, frequency, power factor, demand, and harmonic distortion parameters with revenue-grade accuracy.

Metering System: The ACUVIM II Series advanced multifunction meter supports real-time monitoring and data acquisition for utility and industrial applications. The metering device offers Ethernet and RS-485 communication capabilities with support for Modbus RTU/TCP protocols for integration into SCADA, BMS, and remote monitoring systems.

Insulation System: The MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3 utilizes dry-type insulated CT/PT components for reliable medium voltage metering applications. The system is engineered for low maintenance operation and long service life in demanding outdoor environments.

Primary Connections: The cabinet features 200A separable load-break bushings and fused jumpers insulated for 15 kV service. The primary conducting surfaces are designed for reliable

medium voltage operation with high mechanical and thermal strength.

Secondary Connections: The CT/PT assembly provides accessible terminal blocks and test switch provisions for simplified testing and maintenance procedures. Secondary wiring utilizes solid copper conductors with industry-standard color coding for accurate field identification and installation.


Mount: The MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3 is pad mounted and constructed with a NEMA 3R weatherproof aluminum enclosure suitable for outdoor service conditions.

Benefits: The MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3 Electrical Metering Cabinet provides accurate revenue-grade electrical monitoring for utilities, substations, industrial facilities, and power distribution systems. The integrated ACUVIM II metering platform enables improved energy management, power quality analysis, system diagnostics, and reduced operational costs through advanced monitoring capabilities.


Applications: Utility metering, electrical substations, medium voltage distribution systems, industrial power monitoring, power quality analysis, SCADA integration, energy management systems, utility power generation, power grids, and high voltage system control applications.


Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Side view



Front view






Bottom view


Technical Parameters		
01	Enclosure Color	Munsel™ 7GY 3.29/1.5 Bell Green
02	Enclosure Material	T2.5 Stainless Steel Plate
03	Operating Altitude	≤2000M
04	Operating Environment	Outdoor, floor-mounted
05	Protection Rating	NEMA 3R
06	Wiring Configuration	Bottom Entry & Exit(Cable)
07	Busbar Configuration	Three-Phase Three-Wire,Copper Busbar
08	Connection Cable	
09	Rated Voltage	15kV
10	Rated Current	200A
11	Frequency	60Hz
12	Dimensions Unit	Inches

The unit is converted from millimeters to inches, and the value is rounded to two decimal places.

PT Wiring Diagram



Single Line Diagram



Switchgear Dimensions(W*D*H)		W-59.06*D-49.21*H-59.06	
Switchgear Name		Outdoor Metering Cabinet	
	Equipment Name	Specification	Qty
MC	Current Transformer		3
	Potential Transformer		3
	Cable Connector(mm) 2		
	Voltage Indicator		
	HV Surge Arrester		
Equipment Capacity/Calculated Current			
Cable Type & Spec.(mm)^2			
Remarks			

No.	Name	Type & Spec.	Qty	Note
09				
08	Main Busbar			
07	Outdoor Enclosure	W-59.06*D-49.21*H-59.06	1	
06	Potential Transformer		3	
05	Neutral Grounding Busbar			
04	Voltage Connections		3	
03	Inner Protective Barrier		1	
02	Bushing		9	
01	Current Transformer		3	

LARSON MAGNETICS

9419 E US HWY 175,
KEMP, TX 75143

TITLE

MPD-EMC-R7-3P-GMR-15KV-YT-200.5CT-N3R-M3

DRAWN BY	DATE	REV
CHECKED BY	SHEET # OF	DRAWING #

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs