Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

IND-RLY-2.4A-NO.NC-DM

Bimetallic Mini Overload Relay - 1.6A to 2.4A, 1NO/1NC - Direct Mount, Automatic/Manual Reset

Product ID: 336484

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IND-RLY-2.4A-NO.NC-DM Relay
Unit Type: Bimetallic Mini Overload Relay
Relay Type: Thermal Bimetallic Overload Relay
Dimensions: -
Weight: -
Voltage: -
Full Load Amperage Range: 1.6 – 2.4A
Trip Class: Selectable 10/20
Contacts Arrangement: (1) N/O, (1) N/C
Protection: Ground Fault
Materials: -
Mounting: Direct Mount
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Features/Ratings
Complies with CSA & UL Standards
Automatic & Manual Reset
FFT Approved

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in the USA

The IND-RLY-2.4A-NO.NC-DM from Larson Electronics is a Bimetallic Mini Overload Relay for motor protection in industrial applications. This thermal overload relay features an adjustable ampere range of 1.6A to 2.4A and supports both automatic and manual reset operation. The unit is designed for direct mounting configurations and operates in ambient temperatures ranging from -5°C to 50°C.

The IND-RLY-2.4A-NO.NC-DM is a compact overload relay designed to provide dependable thermal protection for motors and control systems. This unit includes one normally open and one normally closed auxiliary contact for control circuit integration. The relay utilizes bimetallic thermal sensing technology for overload protection and is compliant with CSA and UL standards.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs