Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

IND-RLY-12.16A-240V-NO.NC-DM

Bimetallic Overload Relay - 12A to 16A Adjustable, 1NO/1NC - Direct Mount, 240V AC

Product ID: 336485

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IND-RLY-12.16A-240V-NO.NC-DM Relay
Unit Type: Bimetallic Overload Relay
Relay Type: Bimetallic Manual or Automatic Reset
Reset Type: Automatic / Manual
Dimensions: -
Weight: -
Line Voltage: 240V AC
Full Load Amperage Range: 12A to 16A Adjustable
Contact Rating: 15A
Trip Class: Selectable 10/20
Contacts: (1) N/O, (1) N/C
Protection: Ground Fault
Terminal Type: Screw Terminal
Mounting: Direct Mount
All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Features/Ratings
Electronic Overload Relay

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in the USA

The IND-RLY-12.16A-240V-NO.NC-DM from Larson Electronics is a Bimetallic Overload Relay for industrial motor protection applications. This overload relay features an adjustable ampere range of 12A to 16A and supports both automatic and manual reset operation. The unit is designed for direct mounting installations and is equipped with screw terminals for secure connections.

The IND-RLY-12.16A-240V-NO.NC-DM is a thermal overload relay that utilizes bimetallic sensing technology for reliable overload protection in industrial environments. This unit includes one normally open and one normally closed auxiliary contact with a 15A contact rating. Rated for 240V AC systems, the relay operates within ambient temperatures ranging from -5°C to 50°C and offers dependable protection against overload and phase failure conditions.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson

Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs