Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X

150 kVA Isolation Transformer - 480V Delta Primary - 208Y/120 Wye-N Secondary - NEMA 4X - 60Hz - 316 Stainless Steel Housing

Product ID: 337927



Image: MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X Distribution Transformer
Transformer Type: Distribution
Phase: Three Phase
Frequency: 60 Hz
K Factor: None
kVA: 150
Primary Voltage: 480 V Delta
Taps: 2 x 2.5% FCAN; 4 x 2.5% FCBN
Secondary Voltage: 208Y/120 V Wye-N
Winding Material: Aluminum
Efficiency: 98.83%
Insulation: 180°C
Temperature Rise: 115°C
Impedance: -
Seismic: Yes
Electrostatic Shield: No
Primary Termination: -
Secondary Termination: -
Enclosure Material: NEMA Type 4X Heavy Duty Ventilated - 304 Stainless Steel
Finish: Natural
Dimensions: 41.52"H x 32.90"W x 29.87"D
Weight: 1,400 Lbs
Mounting: Floor Mount

Ratings
Listed for United States and Canada
ANN Cooling
IP14 Rated
UL 1562
Meets or Exceeds U.S. DOE 10 CFR Part 431
C22.2 No. 47

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X 480 V Delta 3 Phase Energy Efficient Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for indoor applications, the MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 150 kVA, the MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X distribution transformer is a three phase unit with a primary voltage of 480 V Delta. It also provides a secondary voltage of 208Y/120 V Wye-N. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA 4X 316 Stainless Steel enclosure makes the unit suitable for indoor applications and it can be floor mounted. The unit also features Class 180°C insulation with a 115°C temperature rise and is rated IP14.

Benefits: The MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X distribution transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Safety: The MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X is a distribution transformer which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-SS-3P-480D-150KVA-208Y.120-N4X achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs