

MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ

**15 kVA Distribution Transformer - 415V Delta Three Phase Primary - 240V Single Phase
Secondary - NEMA 3R - Fully Potted / Encapsulated - 50/60 Hz**

Product ID: 337971



Image: MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ Fully Potted Distribution Transformer

Phase: Three Phase to Single Phase

Frequency: 60 Hz

kVA: 15

Primary Voltage: 415 V Delta 3P

Primary Configuration: Wye

Secondary Voltage: 240 V 1P

Secondary Configuration: N/A

Frequency: 50/60 Hz

Reverse Connectable: Yes

Winding Material: Aluminum

Connection Type: Lugs / Bolt-Down Terminals

Mounting: Wall

Cooling: Air/Dry

Construction Style: Enclosed - Resin Encapsulated Core & Coil

Insulation: 180°C

Temperature Rise: 115°C

Sound Level: Meets NEMA ST-20 Standards

Enclosure Material: NEMA Type 3R Heavy Duty Encapsulated - Steel

Finish: ANSI 61 Grey Finish

Dimensions: 20.2"L x 19.4"W x 21.5"H

Weight: 170 lb

Ratings

NRTL Listed for United States and Canada

IP14 Rated

Fully Potted / Encapsulated

Distribution Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ 415 V Delta Three Phase to Single Phase Energy Efficient Fully Potted Distribution Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ provides increased reliability, protection against critical equipment failures and the ability to adjust the supply voltage to match specific load requirements. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 15 kVA, the MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ fully potted distribution transformer is a three phase to single phase unit with a primary voltage of three phase 415 V Delta. It also provides a secondary voltage of single phase 240 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This encapsulated unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features a 180°C insulation with a 115°C temperature rise.

Benefits: The MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ fully potted distribution transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This fully potted distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated wall mounting brackets make installation fast and easy and the offset outward facing wall installation holes allow for easy power tool access.

Safety: The MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ is an encapsulated isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-FP-3P.1P-415D-15KVA-240V-N3R-50.60HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power



distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.


Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664











Frequently Asked Questions (FAQ)

There are no Faqs