Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

XLE-EL-HF-1411964

1 1/2" NPT Cable Gland – 1.42"– 2.1" Cable Range – Brass, Hazardous Locations

Product ID: 339088



Image: XLE-EL-HF-1411964

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

XLE-EL-HF-1411964 Cable Gland (Straight Cord Connector)
Listing: NRTL Certified for United States, Canada, Europe and International
Unit Type: Cable Gland
Dimensions: Approx. 2" Body Diameter
Weight: tbd
Entry Thread (Hub): 1 1/2" NPT
Minimum Thread Length: N/A
Cable Diameter: 1.42" (Min) to 2.1" (Max)
Operating Temp: -34°C to +107°C
Materials: Brass Body

Ratings
Industrial Grade Construction
Suitable for Wet Locations
Corrosion Resistant
Mechanical Strain Relief
Compression Sealing Design
Environmental Seal
NEMA 4 / 4X / 12 / 13 (When Properly Installed)
ATEX/IECEx

Special Orders - Special Requirements
Contact us for special requirements

Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The Larson Electronics XLE-EL-HF-1411964 Cable Gland provides secure cable entry and strain relief for industrial panels and electrical enclosures. This aluminum cord grip is designed for use with standard 1 1/2" NPT threaded hubs and supports cable outside diameters ranging from 1.42" to 2.1".

The XLE-EL-HF-1411964 is a heavy-duty straight male cord connector built for reliable mechanical retention and environmental sealing in demanding indoor and outdoor

environments. This unit features a 1" NPT male threaded entry and utilizes a compression sealing design to secure flexible cords while maintaining enclosure integrity. Constructed of corrosion-resistant aluminum, the connector is UL 514B listed and CSA certified. When properly installed, it maintains NEMA 4, 4X, 12 and 13 ratings. The cord connector is suitable for operating temperatures ranging from -34°C to +107°C.

Applications: Mechanical cable retention, strain relief for flexible cords, panel and enclosure cable entry, industrial equipment connections, power distribution systems, machine tools, control panels and general cable management applications.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs