Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-DS-FS-FDS-3P-4W-480V-2000A-EF-BM-N3R-TD-M2

Fused Disconnect Switch, 2000 Amp, 480V 3PH AC, 3-Pole 4-Wire, (3) Class L Time Delay Fuses, NEMA 3R

Product ID: 339182



Image: MPD-DS-FS-FDS-3P-4W-480V-2000A-EF-BM-N3R-TD-M2

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-DS-FS-FDS-3P-4W-480V-2000A-EF-BM-N3R-TD-M2 Disconnect Switch - Fused Disconnect

Unit Type: Service Entrance Fused Disconnect Switch
Line-In: N/A (customer provided)
Line-In Cord Cap: N/A (customer provided)
Line-In Connections: Terminal Lugs, Accepts 750MCM-1/0
Line-In Orientation: Bottom Feed
Voltage: 480Y/277V AC
Phase: 3-Phase
Frequency: 60 Hz (60-Cycles)
Configuration: 3-Pole, 4-Wire
Protection Method: Fused, Class L Type Fuse
Protection Type: Time Delay Fuse
Protection Fuses: Included, (3) Fuses
Protection Ampacity: 1600A
Mains Rating (Amps): 2000A
Interrupting Rating: 300 kA @ 480V AC
Disconnect Means: Manual via Handle
Neutral Connection: Included
Ground Fault Protection: Provision for ANSI 50G/51G or 50N/51N Ground Fault Protection
Ground Fault Relay: Adjustable Pickup and Time Delay
Ground Fault CTs: Compatible CTs
Ground Fault Trip: Hardwired Trip Signal
Ground Fault Alarm: Local Indication and Remote Alarm Contacts
Line-Out: N/A (customer provided)

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 891 Dead Front Switch Boards
NEMA 3R Rated for Indoor and Outdoor Use
Made in the USA

Line-Out Cord Cap: N/A (customer provided)
Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0
Line-Out Orientation: Bottom Feed
Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door
Door: (1) Left Hinged Door w/ Padlockable Handle

Mount: Pad Mount

Enclosure Material: 11GA Sheet Steel
Enclosure Finish: ANSI 49 Grey
Enclosure Type: NEMA 3R Ventilated
Dimensions: 43"-W x 36"-D x 90"-H
Weight: 800 lbs
Shipping Dimensions: 58"-W x 44"-L x 98"-H
Shipping Weight: 850 lbs
Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The MPD-DS-FS-FDS-3P-4W-480V-2000A-EF-BM-N3R-TD-M2 from Larson Electronics is a Power Distribution Disconnect Switch that is designed for reliable, safe, and convenient power distribution at industrial work sites. This fused disconnect includes three 1600-amp 480V rated Class L fuses. Designed for floor mounting installations, the bottom feed disconnect switch is protected by a NEMA 3R rated, steel enclosure with a ventilated design.

The MPD-DS-FS-FDS-3P-4W-480V-2000A-EF-BM-N3R-TD-M2 service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with three-phase 480V AC Delta or Wye, the disconnect switch features a manual operating handle. This bottom feed disconnect carries a 200 kA at 480V AC interrupt rating. The switchgear comes with and accepts three 1600-amp 480V rated Class L time delay fuses. An insulated grounded neutral kit with bond strap is included for neutral connections.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power. A dead front cover protects operators from the fuses for safety. Operators can inspect the fuses through the dead front via a vented cover. Removing the dead front allows access to the fuses.

Time Delay vs. Fast Acting Fuses Two of the most common types of fuses found in power distribution equipment are time delay and fast acting fuses.

> **Time Delay:** Time delay fuses are tripped once overcurrent heat builds up enough to melt the fuse element over a period of time. That period of time varies between different time delay fuses depending on the application. Time delay fuses decrease the chances of false tripping. During startup, many components require a large current for a very short amount of time. In other words, a time delay fuse disconnects the circuit only when the overcurrent persists in the line.
>
> **Fast Acting:** Fast acting fuses are tripped immediately upon sensing an overcurrent or short circuit in the line. They are ideal for electronics, components, or systems that cannot withstand sudden changes in current. A fast acting fuse will not withstand a temporary overload such as one that occurs during the startup process.

Enclosure Design: The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI 49 grey finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor and outdoor areas.

Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the service entrance disconnect on floors and flat surfaces.

Customization: The MPD-DS-FS-FDS-3P-4W-480V-2000A-EF-BM-N3R-TD-M2 can be customized to meet specific operating and power requirements. Example of customization includes:

• Making the fused disconnect portable and certified to NRTL UL 1640 for portable equipment

• Adding single pole camlock connectors for quick connections

• Adding heaters for cold environments

• Aiding alarm relays for trip notification downstream

• Adding power meters

Applications: This disconnect switch is suitable for indoor/outdoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs