Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-MV-PT-R7-A11-GMA-57KV-SX.LM-C0.3WXYZZZM-Z-60HZ-OL-OD-M1

57 kV Potential Transformer, Oil Filled - 34,500V Primary, 115/69V Secondary, 300:1 Ratio, 0.3 WXYZ, ZZ Accuracy Class, Light Gray, Outdoor

Product ID: 339956



Image: MT-MV-PT-R7-A11-GMA-57KV-SX.LM-C0.3WXYZZZM-Z-60HZ-OL-OD-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-MV-PT-R7-A11-GMA-57KV-SX.LM-C0.3WXYZZZM-Z-60HZ-OL-OD-M1 Potential Transformer

Unit Type: Potential Transformer
Application: Revenue Metering, Relaying & SCADA
Phase: Single Phase
Primary Voltage: 34500Y/19920
Primary Voltage Class: 57 kV
Primary Phasor: Grounded Wye
Primary BIL: 350 kV
60 Hz, 1 min. Withstand Voltage: 140 kV (Wet) / 165 kV (Dry)
Primary to Secondary Ratio: 300:1
Secondary Voltage: 115/69V
Frequency: 60 Hz
No. Of Bushings: (1)
Rated Voltage Factor: 1.2 Continuous
ANSI Accuracy Class Operation at Rated Voltage (Metering Accuracy): 0.3 W, X, Y, Z, ZZ, M
Cooling Class: ONAN Self-Cooled
Insulator Type: Porcelain or Composite
Primary Connection: High Voltage Terminal
Primary Overcurrent Protection (OCP): Non-Fused
Secondary Connection: Terminal Block

Ratings

Meets IEEE C57.13 Standard
Meets BPA Specification 22-07
Outdoor Service
Non-corroding Stainless Steel Nameplate

Secondary Terminal Box: Weatherproof

Space Heater: N/A

Winding Material: Copper

Nameplate Material: Stainless Steel with IEEE 693 Seismic Identification Plate

Operating Temperature Range: -40°C to +40°C
Average Temperature Rating (24 hrs): +40ºC
Service Condition: Outdoor
Finish: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)
Housing Materials: Welded Steel Oil-Filled Tank
Mount: Base / Structure Mounted
Total Dimensions: TBD
Total Weight: TBD

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-MV-PT-R7-A11-GMA-57KV-SX.LM-C0.3WXYZZZM-Z-60HZ-OL-OD-M1 Potential Transformer from Larson Electronics is designed for outdoor utility and substation applications requiring highly accurate voltage measurement for revenue metering, monitoring, protective relaying, and SCADA systems. This 57kV-class, oil-filled, wound-type instrument transformer is engineered for reliable operation on 34.5kV grounded-wye power systems and delivers exceptional accuracy, rugged construction, and long service life in demanding transmission and distribution environments.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The potential transformer is rated for a 34,500Y/19,920V grounded wye primary and 115/69V secondary with a 300:1 transformation ratio. The unit features a 350kV Basic Insulation Level (BIL) and ANSI/IEEE 0.3 W, X, Y, Z, ZZ, M metering accuracy at 60Hz. Constructed with heavy-duty copper windings and a hermetically sealed oil-filled insulation system, the transformer provides excellent dielectric strength, superior thermal performance, and dependable long-term reliability. The unit complies with IEEE C57.13 and BPA Specification 22-07, and is qualified to IEEE 693-2018 High Seismic Level requirements with a seismic identification plate.

Primary Connections: The transformer is equipped with a single high-voltage primary bushing and a tinned copper high-voltage terminal suitable for utility substations and outdoor transmission installations.

Secondary Connections: The potential transformer is furnished with a weatherproof secondary terminal compartment containing corrosion-resistant terminal blocks for secure field wiring, metering, relaying, and maintenance access.

Benefits: The MT-MV-PT-R7-A11-GMA-57KV-SX.LM-C0.3WXYZZZM-Z-60HZ-OL-OD-M1 transformer delivers precise voltage transformation for revenue metering, protective relaying, and SCADA applications while minimizing maintenance requirements and ensuring dependable long-term operation. Its hermetically sealed oil-filled construction provides superior insulation performance, moisture resistance, and environmental protection, making it ideal for utility substations and high-voltage transmission systems operating in harsh outdoor conditions.

Applications: Electric utilities, transmission substations, distribution substations, switchyards, renewable energy facilities, power generation stations, revenue metering, protective relaying,

SCADA monitoring, transmission and distribution networks, voltage monitoring, and high-voltage power system control.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs