

RFUSE-E-5KV-15A-TD

Class E Time-Delay Fuse, 5kV AC, 15A Rated

Product ID: 341648



Image: RFUSE-E-5KV-15A-TD

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RFUSE-E-5KV-15A-TD Class E Time-Delay Fuse

Current Rating: 15A
Voltage Rating AC: 5kV
Fuse Class: Class E
Interrupting Rating: 10kA @ 5kV AC
Body Style: Ceramic Cartridge Fuse
Construction: Melamine/Ceramic Tube with Nickel-Plated End Caps
Mounting Style: Fuse Holder (Class-E Fuse Block)
Termination Style: Clip
Operating Temperature: -40°C to +85°C
Indicator: Without

Dimensions & Shipping

Overall Dimensions: 1-1/16 in Diameter × 8.5 in Length (estimated)
Approximate Weight: 0.75 lb each (estimated)
Shipping Dimensions: TBD
Shipping Weight: TBD

Made in the USA

Features

Time-delay characteristic reduces false tripping during startup
Current-limiting design

Shipping

Shipped via standard parcel
Crated shipment available upon request
Final shipping configuration subject to approved design

Special Orders – Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

Made in the USA

The RFUSE-E-5KV-15A-TD from Larson Electronics is a Class E Time-Delay Fuse rated 5kV AC, 15A. This fuse is designed for use in medium-voltage current-limiting fuse applications, providing a 10kA interrupting rating at 5kV AC.

Construction:

The fuse utilizes a ceramic cartridge body style, constructed from a melamine/ceramic tube with nickel-plated end caps. Termination is via clip-style contacts, compatible with a Class E fuse block/holder.

Operation:

This time-delay fuse is designed to withstand momentary overcurrent conditions, such as those encountered during equipment startup, while still providing reliable interruption during sustained fault conditions. The fuse operates across a temperature range of -40°C to $+85^{\circ}\text{C}$.

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and applicable drawings.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs