Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ

6 kVA Isolation Transformer - 380Y/220V Wye Primary Voltage - 220V Delta Secondary Voltage - 50 Hz - NEMA 3R

Product ID: 342300



Image: MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ Fully Potted Isolation Transformer

Phase: Three Phase
Frequency: 50 Hz
kVA: 6
Primary Voltage: 380Y/220V AC, 3 Phase + Neutral, 4-Wire
Secondary Voltage: 220V AC, Delta, 3 Phase + Earth
Taps: 2 x 5% FCAN; 2 x 5% FCBN
Impedance: -
Winding Material: Aluminum
Primary Termination (Std): -
Secondary Termination (Std): -
Mounting: Floor
Cooling: Air/Dry
Insulation: 180°C
Temperature Rise: 115°C
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 3R Heavy Duty - Steel
Finish: ANSI 61 Grey, UL50 Finish
Dimensions: 18.86"H x 20.30"W x 9.03"D
Weight: 250 lb

Approvals/Ratings

Listing: UL Listed
CSA Certified
Isolation Transformer
Fully Potted
C22.2 No. 47
UL 506

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ 380Y/220 V Wye 3 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful,

reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 6 kVA, the MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ transformer is a fully potted three phase unit with a primary voltage of 380Y/220 V Wye. It also provides a secondary voltage of 220 V Delta. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 180°C insulation with a 115°C temperature rise.

Benefits: The MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ fully potted general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This fully potted transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor mounting brackets make installation fast and easy.

Safety: The MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-FP-3P-380Y.220-6KVA-220D-N3R-50HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs